Journal of Mines, Metals and Fuels, *73(7): 2137-2145; 2025. DOI: 10.18311/jmmf/2025/49125*

Print ISSN : 0022-2755

Journal of Mines, Metals and Fuels

Contents available at: *www.informaticsjournals.co.in/index.php/jmmf*

AI-Driven Smart Dam Management System for Enhanced Safety and Flood Prevention

Bharat Nirmal * and Swati Shekapure

Department of Computer Engineering, Marathwada Mitramandal's College of Engineering, Karvenagar, Pune - 411052, Maharashtra, India; india.nirmal77@gmail.com

Abstract

Water is essential to everyday life and plays a vital role across various sectors. With the growing challenges related to water management, innovative approaches such as adaptive strategies, remote sensing technologies, and integrated water security frameworks are being developed. Dam safety has become increasingly important due to the ageing of infrastructure, seismic risks, and the intensifying impacts of extreme weather events. As a result, it has emerged as a key focus area within national disaster management plans. Governments are introducing regulatory frameworks, and institutions are adopting technical and structural safeguards to ensure dam integrity. However, a major concern remains—the absence of standardised emergency water release protocols. To address this, the project proposes an AI-powered dam monitoring and control system utilising a Stacked Dense LSTM (Long Short-Term Memory) model. This system analyses real-time data on water levels, temperature, humidity, and rainfall, which are stored in the cloud. The LSTM model predicts potential threats and manages water discharge through automated gate control, reducing the risk of dam overflow and flooding. Sudden floods caused by rising rivers, heavy rainfall, or lake overflow can lead to widespread destruction, displacing families, damaging agriculture, and causing long-term disruptions. The proposed predictive system enables proactive dam management, significantly reducing flood risks and enhancing the resilience of vulnerable communities.

Major Findings: *The AI-driven Smart Dam Management System proposed in the study effectively addresses critical challenges in flood prevention and dam safety by utilising a Stacked Dense LSTM model for real-time water level prediction and automated gate control. Through the integration of environmental sensors, cloud-based data storage, and intelligent analytics, the system enhances forecasting accuracy, mitigates overflow risks, and ensures timely interventions. The findings highlight its transformative potential in improving community resilience, supporting sustainable water resource management, and bridging existing gaps in emergency response protocols.*

Keywords: *AI-Driven Dam Management, Automated Water Release, Climate Resilience, Cloud-Based Data Storage, Community Resilience, Dam Safety, Disaster Management, Emergency Protocols, Flood Mitigation, Predictive Analytics, Real-Time Monitoring, Stacked Dense LSTM Model, Water Flow Prediction, Water Management*

1.0 Introduction

Water is an indispensable resource that supports daily life and drives key sectors such as agriculture, energy production, and industry. However, climate change, ageing infrastructure, and extreme weather events have intensified the challenges associated with water management. Among these concerns, dam safety has emerged as a critical priority, as the risks of structural failures, uncontrolled water releases, and devastating floods continue to grow. Governments and disaster management agencies have implemented regulatory measures and institutional safeguards to enhance dam safety. However, a significant gap remains in the standardisation of water release

*Author for correspondence




Figure 1. Smart water management.

protocols, particularly in emergencies. Traditional dam management approaches rely on historical data, manual decision-making, and reactive strategies, which may be insufficient in rapidly evolving conditions. To address these challenges, this project proposes an AI-driven dam management system that leverages a Stacked Dense Long Short-Term Memory (LSTM) model to improve predictive capabilities in dam operations. The system integrates real-time environmental monitoring, including water levels, temperature, humidity, and rainfall, storing and analysing this data in a cloud-based infrastructure for efficient processing and decision-making. By utilising machine learning techniques, the system predicts water flow dynamics and automates the controlled release of water through dam gates, mitigating the risks of overflow and flooding. Figure 1 explains Smart Water Management.

Flooding, often caused by excessive rainfall and rising water levels, poses severe risks to communities, infrastructure, and livelihoods. The proposed AI-driven system offers a proactive and data-driven approach to dam safety, improving disaster preparedness and response efficiency. By enabling timely and automated decision-making, this solution enhances community resilience and ensures sustainable water management in the face of environmental uncertainties.

2.0 Literature Review

A digital twin platform has been developed to revolutionise dam and watershed management by enabling real-time monitoring and simulation of dam operations. This innovative approach supports predictive maintenance and optimises resource utilisation, contributing to more informed and timely decision-making during critical scenarios. By creating a detailed virtual replica of dam structures and their surrounding environmental conditions, the platform facilitates continuous data analysis, enhancing proactive safety strategies and operational efficiency[1]. This study investigates the application of advanced instrumentation in dams, highlighting the crucial role of real-time data collection and monitoring in maintaining dam safety. Instruments such as piezometers, inclinometers, and seismic sensors are utilised to track structural variations and assess parameters like water levels, seepage, and internal pressure. By delivering continuous and accurate data, these monitoring tools serve as an effective early warning system, enabling timely interventions and reducing the risk of catastrophic dam failures[2]. The study reviewed dam renovation techniques such as sediment removal, spillway expansion, and ecological restoration to extend reservoir life, address ageing infrastructure, and reduce environmental impacts for sustainable water management[3]. The study emphasised the vital need for monitoring tailings dams—prone to structural failure—through methods like visual inspections, geotechnical tools, and safety audits to enhance their stability and minimise associated risks[4]. The study introduced a data assimilation method that leverages real-time hydrological data and predictive analytics to enhance flood forecasting and optimise reservoir water release, reducing downstream flood risks[5]. The study used remote sensing and GIS to identify optimal dam construction sites in the Jhelum Basin, highlighting the importance of strategic site selection in flood risk mitigation and ecological preservation[6]. The study explored the socio-ecological effects of building a multi-stage flood control system on tributaries, revealing that although such systems help reduce flood risk, they can also disrupt local ecosystems and impact nearby communities. It highlights the need to balance flood management with environmental and social sustainability in infrastructure planning[7]. The study examined the use of Artificial Intelligence and Internet of Things (AIoT) technologies in monitoring fill dams to improve operational performance. It emphasises that AIoT enables real-time monitoring and predictive maintenance, minimising the chances of structural

failure while offering valuable insights to enhance safety and efficiency in dam operations[8]. The study analysed the growing trend of dam removals in the U.S., assessing infrastructure preparedness and the environmental advantages of such actions. It underscores the multifaceted nature of dam removal decisions, involving ageing structures, ecological restoration, and water management strategies, contributing to the broader discussion on aligning dam safety with environmental sustainability[9]. Water management is increasingly challenged by climate change, ageing infrastructure, and extreme weather, with dam safety becoming a critical concern due to risks of structural failures and uncontrolled water releases[10]. Traditional dam management relies on historical data and manual decision-making, proving insufficient in rapidly evolving conditions[11]. An AI-driven dam management system using a Stacked Dense Long Short-Term Memory model is proposed to improve predictive capabilities in dam operations and address these issues. The system integrates real-time environmental monitoring, storing and analysing data in a cloud-based infrastructure for efficient processing and decision-making to predict water flow dynamics and automate controlled water releases, mitigating overflow and flooding risks. Flooding caused by excessive rainfall and rising water levels poses severe risks to communities, infrastructure, and livelihoods, necessitating proactive and data-driven approaches to dam safety that improve disaster preparedness and response efficiency. The integration of machine learning techniques offers a transformative approach to enhance community resilience and ensure sustainable water management amidst environmental uncertainties[12]. Data-driven and machine learning methods, with their improved accuracy, are affecting a variety of real-life applications, encouraging the use of such methodologies as core drivers for streamflow forecast and inundation models[13]. Artificial intelligence and machine learning have become essential instruments for understanding non-linear systems and generating flood predictions, improving both accuracy and reducing computational time and model development costs[14]. One method integrates a long short-term memory network, Bayesian optimisation, and transfer learning techniques to create a data-driven model for flood predictions in both temporal and spatial dimensions, which could support decision-making for flood management[15]. AI models that use long short-term memory networks can predict daily streamflow, and are being implemented in open-source repositories[16]. Flood prediction systems utilising machine learning models can assess flood probabilities based on location and time queries and can integrate with multi-model deep learning methods such as Support Vector Machines, Neural Networks, and Extreme Learning Models, predicting flood chances based on environmental, climatic, and geographical factors. It is possible to forecast flood warnings with sufficient lead time for decision making by developing Flood Early Warning Systems[17]. Deep learning techniques are being used increasingly in flood management to overcome the limitations of accurate, but slow, numerical models, and to improve the results of traditional methods for flood mapping[18]. The incorporation of AI and machine learning technologies enhances environmental protection efforts, aiding in climate change mitigation, biodiversity conservation, waste reduction, water security, and clean air initiatives[19]. AI can be used for various scientific disciplines such as energy applications, manufacturing, and health. Water resource management and drinking water quality can be improved by using machine learning to forecast water quality and quantity[20]. Data-driven approaches like artificial neural networks have emerged as valuable tools for forecasting water resource variables because they can learn relationships between variables by applying special training algorithms on available data[21]. Machine learning is widely applied in drinking water treatment and management systems, including drinking water source management, treatment processes, water distribution, and decision making[22]. AI algorithms can be trained on past data to predict hazardous material releases and environmental pollution, and AI solutions for environmental monitoring can include early warning systems for hazardous material release, autonomous pollution monitoring systems, and decision support systems[23]. AI can predict necessary parameters that are otherwise difficult to determine experimentally[24].

Several critical research gaps persist in the domain of dam management and safety monitoring. Standardised protocols for data collection and analysis are largely absent, making regional comparisons difficult and inconsistent. The integration of heterogeneous data sources for holistic risk assessments remains limited, and

there is a need to explore the scalability and contextual adaptability of AI and IoT-based solutions. Additionally, there is insufficient research on the long-term effectiveness of technologies such as digital twins and AI-driven systems, along with a lack of emphasis on community involvement in dam-related decision-making. Ecological impacts of dam operations are often overlooked, and predictive modelling that incorporates climate variability requires further development. Moreover, practical barriers to implementing digital twin platforms and a lack of empirical studies on the effects of dam removal highlight areas requiring deeper investigation. Bridging these gaps is vital for advancing dam safety and building robust, resilient water management frameworks.

3.0 Problem Statement

The increasing frequency and intensity of extreme weather events, ageing infrastructure, and the growing complexities of water resource management pose significant challenges to dam safety and flood mitigation. Existing dam management systems cannot often integrate real-time data from diverse sources, hindering their ability to make timely and informed decisions during critical situations. Furthermore, the absence of standardised protocols for emergency water release increases the risk of dam failures and associated flooding, which can devastate communities and ecosystems. This project aims to address these challenges by developing an AI-driven dam management system that leverages advanced predictive modelling, data integration, and community engagement to enhance decision-making processes. By implementing a Stacked Dense LSTM model, the system will provide real-time insights and automated solutions for water management, ultimately improving the resilience of communities facing the risks of flooding and ensuring the safety of dam infrastructure.

4.0 Proposed System

The AI-driven dam management system operates by collecting and analysing real-time data on water levels, temperature, humidity, and rainfall, using a network of sensors installed around the dam. This data is then transmitted wirelessly to a base station, where it is aggregated, pre-processed, and formatted. From the base station, the data is uploaded to a cloud server, enabling authorities to access it instantly. At the command centre, advanced AI algorithms, such as a Stacked Dense LSTM model, analyse the data to detect trends and potential risks. The system continuously checks water levels against predefined safety thresholds. If the water level surpasses a critical threshold, the AI model signals the need to open the dam gates to release excess water, preventing overflow. Conversely, if water levels remain below the threshold, the gates are kept closed to retain water.




Figure 2. System architecture.

This decision-making process may be automated, with the AI model directly controlling gate operations, or semi-automated, where recommendations are provided to human operators. A feedback loop ensures that the command centre receives ongoing data updates after each gate operation, enabling continuous monitoring and adjustments. Over time, the AI system refines its threshold criteria based on historical data, enhancing predictive accuracy and resilience. This approach ensures efficient, dynamic dam management, mitigating flood risks while optimising water retention. Figure 2 illustrates the overall system architecture of the proposed AI-Driven Smart Dam Management System. It outlines the flow of data and decision-making process from initial data collection to automated or semi-automated dam gate control.

The architecture begins with input sensors installed at strategic locations around the dam, which continuously monitor environmental parameters such as water level, rainfall, temperature, and humidity. These real-time measurements are transmitted wirelessly to a base station, where the data is collected, aggregated, and pre-processed for further analysis. Once formatted, the data is uploaded to a cloud-based server, enabling remote access and real-time monitoring by relevant authorities and stakeholders through a central command centre. Within this control hub, the system leverages a Stacked Dense LSTM model—a powerful deep learning algorithm—to analyse the incoming data and detect emerging trends or threshold breaches.

Based on the AI model's output, the system makes critical decisions regarding dam gate operations:

- If water levels rise above a predefined safety threshold, the system triggers gate opening to release excess water and prevent overflow.
- If water levels remain within safe limits, the gates remain closed to conserve water.

This process may be fully automated or involve human operators reviewing AI-generated recommendations before acting. A feedback loop ensures that the command centre receives updated sensor data post-execution, allowing the system to adapt and refine its responses over time. In essence, Figure 2 visualises how the integration of sensors, wireless communication, cloud computing, and AI works together to support efficient, real-time, and intelligent dam management for flood risk reduction and water resource optimisation.

5.0 Algorithm - Stacked Dense LSTM Water Level

The Stacked Dense Long Short-Term Memory (LSTM) algorithm is a sophisticated machine learning technique designed for analysing and predicting time-series data, particularly in the context of water level management for dams. LSTMs address the limitations of traditional recurrent neural networks (RNNs), notably the vanishing gradient problem, which impedes the learning of long-term dependencies in sequential data. By employing a unique architecture that includes memory cells, LSTMs can store and manipulate information over extended periods, allowing them to effectively capture




Figure 3. Stacked dense LSTM water level.

complex temporal patterns in datasets. The architecture consists of multiple stacked LSTM layers, where each layer learns different features from the input data, enabling hierarchical understanding of temporal relationships.

The model begins with an input layer that processes historical data such as water levels, rainfall, humidity, and temperature, which are normalised for better training efficiency. The core stacked LSTM layers focus on learning both short-term and long-term dependencies, while memory cells manage the information flow through input, forget, and output gates. Following these layers, dense layers combine the outputs for final predictions, ultimately producing the anticipated water levels. Figure 3 visually demonstrates how deep learning techniques, particularly the Stacked Dense LSTM architecture, are structured to process complex environmental data and provide highly accurate water level forecasts. These predictions enhance dam safety by supporting automated, timely, and reliable decision-making in response to potential flood threats. Training involves preparing historical data into sequences, employing a loss function like Mean Squared Error (MSE), and using optimisers such as Adam to adjust model weights. Once trained, the Stacked Dense LSTM can predict future water levels based on real-time data, significantly enhancing dam management practices and aiding in flood risk mitigation. By analysing incoming

environmental data, the model provides accurate forecasts that enable timely operational adjustments, preventing overflow and minimising downstream flood damage. Overall, the Stacked Dense LSTM represents a cutting-edge solution in predictive analytics for dam management, enhancing safety measures and decision-making processes while bolstering community resilience against flood-related disasters.

6.0 Result and Discussion

Figure 4 presents the Graphical User Interface (GUI) of the AI-Driven Smart Dam Management System, designed for intuitive interaction and operational efficiency. The interface features clearly labelled, user-friendly buttons that facilitate key functionalities such as system testing, prediction execution, performance evaluation, and result summarisation. These options are seamlessly integrated over a visually appealing background image of a large dam, reinforcing the application's context and purpose. The layout ensures ease of use for technical as well as non-technical users, thereby enhancing accessibility and user experience.



Figure 4. AI-driven smart dam management system interface.

Figure 5 depicts a histogram representing the frequency distribution of daily readings for the monitored variable "Stage_1_2". The histogram shows that lower values occur more frequently, with the frequency gradually diminishing as the values increase. This pattern reflects a right-skewed distribution, indicating that extremely high values are less common while most observations are clustered toward the lower end of the scale. This insight can help in identifying operational norms and potential anomalies in water stage levels.

Figure 6 shows the estimated Probability Density Function (PDF) of a variable derived through kernel density estimation. The curve exhibits a prominent and narrow peak at the centre, which indicates that a large number of values are closely concentrated around the mean. This distribution exhibits leptokurtic characteristics, meaning it has higher kurtosis than a normal distribution. Such a shape suggests low variability around the mean with occasional outliers, which is crucial




Figure 5. Histogram of daily Stage_1_2 values.

for assessing the stability and reliability of dam-related variables in predictive models.

Figure 7 demonstrates the temporal variation in demand, specifically for the Stage_1_2 variable, over a continuous period ranging from early 1996 to early 1998. The plotted data reveals substantial fluctuations in demand, characterised by numerous sharp and irregular peaks throughout the timeline. These peaks are particularly prominent during early 1996 and again in late 1997, signifying periods of heightened demand and increased volatility in the system. Such fluctuations may reflect dynamic environmental conditions, operational shifts, or external influences impacting dam behaviour.




Figure 6. Kernel density estimation plot.

Moreover, a gradual but noticeable decline in demand is observed as the timeline approaches the beginning of 1998, suggesting a potential stabilisation phase or reduction in water flow requirements. This downward trend could indicate seasonal effects, improved management strategies, or changes in hydrological input variables. Overall, the figure emphasises the non-linear and highly variable nature of dam demand patterns, which are critical for planning, forecasting, and real-time decision-making in smart dam operations.

Figure 8 presents a line plot comparison between two distinct datasets, both of which are crucial for assessing dam safety through the use of Artificial Intelligence (AI). This comparative visualisation helps to evaluate the accuracy and reliability of AI-driven predictions against real-world sensor data. The blue line in the graph represents a continuous stream of real-time data, likely obtained from sensors embedded within the dam infrastructure. These sensors monitor various parameters such as water pressure, structural movement, seepage, or reservoir level, providing an authentic and dynamic view of the dam's operational condition over time. In contrast, the red line signifies a second data source, which may include forecasted or modelled values generated by the AI system. This dataset could reflect predicted conditions, safety thresholds, or baseline performance levels, offering a reference against which the actual sensor data is assessed. The alignment or deviation between the two lines offers valuable insights into system performance. When the blue line (actual data) closely follows the red line (predicted/ threshold data), it indicates that the system is performing




Figure 7. Time series plot of Stage_1_2 demand (1996-1998).




Figure 8. Line plot comparison of two data series.

within expected limits. However, any significant divergence between the lines, particularly when the blue line crosses critical thresholds, may signal potential risks, anomalies, or performance deviations, thereby triggering alerts for further inspection or preventive action. This dual-line representation is vital for ensuring proactive monitoring, early warning, and data-driven decision-making in smart dam safety management.

7.0 Conclusion

The development and implementation of the AI-driven Smart Dam Management System based on the Stacked Dense LSTM model represents a transformative step toward modernising water resource management and enhancing dam safety. This system effectively addresses longstanding challenges posed by ageing dam infrastructure, unpredictable climatic events, and the lack of real-time, data-informed decision-making processes in traditional dam operations. By integrating continuous environmental data inputs such as water levels, rainfall, humidity, and temperature through a network of IoT-enabled sensors, the system enables highly accurate forecasting of flood risks. The predictive capabilities of the LSTM model empower the system to autonomously regulate dam gate operations, ensuring timely water release during potential overflow conditions while optimising water retention under normal scenarios. This dynamic and intelligent control significantly reduces the risk of catastrophic flooding, improves response times, and enhances community resilience against natural disasters. Moreover, the system addresses a major gap in dam management—the absence of standardised emergency water release protocols—by offering automated and adaptive decision-making frameworks that operate in real time. Its user-friendly interface, cloud-based architecture, and feedback loop ensure operational transparency and continuous improvement through self-learning algorithms. In addition to its technical innovation, the system supports sustainable development goals by promoting climate resilience, protecting ecosystems, and safeguarding lives and livelihoods. It also sets a precedent for the broader application of AI in disaster risk reduction and infrastructure monitoring. Future work may explore extending the platform to multi-dam networks, incorporating advanced hybrid AI models, integrating socio-environmental impact assessment modules, and fostering greater stakeholder and community participation in dam safety strategies.

8.0 References

1. Park D, You H. A digital twin dam and watershed management platform. Water. 2023; 15(11):2106. https://doi.org/10.3390/w15112106
2. Adamo N, Al-Ansari N, Sissakian V, Laue J, Knutsson S. Dam safety: Use of instrumentation in dams. J Earth Sci Geo Eng. 2021; 11(1):145-202. https://doi.org/10.47260/jesge/1115
3. Kondolf M, Yi J. Dam renovation to prolong reservoir life and mitigate dam impacts. Water. 2022; 14(9):1464. https://doi.org/10.3390/w14091464
4. Adamo N, Al-Ansari N, Sissakian V, Laue J, Knutsson S. Dam safety: Monitoring of tailings dams and safety reviews. J Earth Sci Geo Eng. 2021; 11(1):249-289. https://doi.org/10.47260/jesge/1117
5. Zhang J, Cai X, Lei X, Liu P, Wang H. Real-time reservoir flood control operation enhanced by data assimilation. J Hydrol. 2021; 598:126426. https://doi.org/10.1016/j.jhydrol.2021.126426
6. Rather MA, Meraj G, Farooq M, Shiekh BA, Kumar P, Kanga S, *et al.* Identifying the potential dam sites to avert the risk of catastrophic floods in the Jhelum Basin, Kashmir, NW Himalaya, India. Remote Sensing. 2022; 14(7):1538. https://doi.org/10.3390/rs14071538

7. Vahedifard F, Madani K, AghaKouchak A, Thota SK. Are we ready for more dam removals in the United States? Environ Res: Infrastruct Sustain. 2021; 1(1):013001. https://doi.org/10.1088/2634-4505/abe639
8. Podgornov NS, Davydov RV, Zotov DK, Antonov VI, Maslikov VI, Maslikova EI, *et al*. Socio-ecological consequences during the construction of a multistage system of flood control facilities on side tributaries. J Phys Conf Ser. 2021; 1942(1):012059. https://doi.org/10.1088/1742-6596/1942/1/012059
9. Kong SM, Yoo C, Park J, Park JH, Lee SW. AIOT monitoring technology for optimal fill dam installation and operation. Appl Sci. 2024; 14(3):1024. https://doi.org/10.3390/app14031024
10. Ye X, Wang S, Lu Z, Song Y, Yu S. Towards an AI-driven framework for multi-scale urban flood resilience planning and design. Comput Urban Sci. 2021; 1(1):11. https://doi.org/10.1007/s43762-021-00011-0
11. Choi JH, Jun C, Liu P, Kim J, Moon Y. Resolving emerging issues with aging dams under climate change projections. J Water Res Plan Manag. 2020; 146(5). https://doi.org/10.1061/(ASCE)WR.1943-5452.0001204
12. Bonafilia D, Tellman B, Anderson T, Issenberg E. Sen1Floods11: A georeferenced dataset to train and test deep learning flood algorithms for Sentinel-1. 2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), 2020 Jun 14-19, Seattle, WA, USA; 2020. https://doi.org/10.1109/CVPRW50498.2020.00113
13. Nevo S, Morin E, Rosenthal AG, Metzger A, Barshai C, Weitzner D, *et al*. Flood forecasting with machine learning models in an operational framework. Hydrol Earth Syst Sci. 2022; 26(15):4013-4032. https://doi.org/10.5194/hess-26-4013-2022
14. Zeng C, Bertsimas D. Global flood prediction: A multimodal machine learning approach. arXiv (Cornell University). 2023.
15. Zhou Q, Teng S, Situ Z, Liao X, Feng J, Chen G, *et al*. A deep-learning-technique-based data-driven model for accurate and rapid flood predictions in temporal and spatial dimensions. Hydrol Earth Syst Sci. 2023; 27(9):1791-1808. https://doi.org/10.5194/hess-27-1791-2023
16. Nearing G, Cohen D, Dube V, Gauch M, Gilon O, Harrigan S, *et al*. Global prediction of extreme floods in ungauged watersheds. Nature. 2024; 627(8004):559-563. https://doi.org/10.1038/s41586-024-07145-1
17. Mosavi A, Öztürk P, Chau K. Flood prediction using machine learning models: Literature review. Water. 2018; 10(11):1536. https://doi.org/10.3390/w10111536
18. Bentivoglio R, Isufi E, Jonkman SN, Taormina R. Deep learning methods for flood mapping: A review of existing applications and future research directions. Hydrol Earth Syst Sci. 2022; 26(16):4345-4378. https://doi.org/10.5194/hess-26-4345-2022
19. Hojageldiyev D. Artificial intelligence opportunities for environmental protection. Paper presented at the SPE Gas & Oil Technology Showcase and Conference, Dubai, UAE; 2019. https://doi.org/10.2118/198616-MS
20. Feng F, Zhang Y, Chen Z, Ni J, Feng Y, Xie Y, *et al*. Machine learning to access and ensure safe drinking water supply: A systematic review. J Environ Chem Eng. 2024. https://doi.org/10.26434/chemrxiv-2024-cc4jd-v2
21. Wünsch A, Liesch T, Broda S. Forecasting groundwater levels using nonlinear autoregressive networks with exogenous input (NARX). J Hydrol. 2018; 567:743-758. https://doi.org/10.1016/j.jhydrol.2018.01.045
22. Essamlali I, Nhaila H, Khaïli ME. Advances in machine learning and IoT for water quality monitoring: A comprehensive review. Heliyon. 2024; 10(6). https://doi.org/10.1016/j.heliyon.2024.e27920
23. Shishegar S, Duchesne S, Pelletier G, Ghorbani R. A smart predictive framework for system-level stormwater management optimization. J Environ Manag. 2020; 278:111505. https://doi.org/10.1016/j.jenvman.2020.111505
24. Kamali M, Appels L, Yu X, Aminabhavi TM, Dewil R. Artificial intelligence as a sustainable tool in wastewater treatment using membrane bioreactors. Chem Eng J. 2020; 417:128070. https://doi.org/10.1016/j.cej.2020.128070