Journal of Mines, Metals and Fuels, *73(8): 2427-2437; 2025. DOI: 10.18311/jmmf/2025/49404*

Print ISSN : 0022-2755

Journal of Mines, Metals and Fuels

Contents available at: *www.informaticsjournals.co.in/index.php/jmmf*

The Evolution of Additive Manufacturing in Sustainable Biomaterial Production

Rajesh Kamalkishor Mantri[1], Avinash T. Gatade[2], Rahul R. Chakule[3], Sagarkumar J. Aswar[4], Yugesh A. Kharche[5], Nilesh Khandare[6] and Devakant Baviskar[7*]

[1]Department of Mechanical Engineering, Government Polytechnic, Khamgaon - 444303, Maharashtra, India
[2]Pillai HOC college of Engineering and Technology, Mumbai University, Mumbai - 410207, Maharashtra, India
[3]Mechanical Engineering Department, Loknete Gopinathji Munde Institute of Engineering Education and Research, Nashik - 422022, Maharashtra, India
[4]Department of Automation and Robotics, MET's Bhujbal Knowledge City, Nashik - 422003, Maharashtra, India
[5]Department of Mechanical Engineering, Padmashri Dr. V. B. Kolte College of Engineering Malkapur - 443101, Maharashtra, India
[6]Department of Mechanical Engineering, Shri Sant Gajanan Maharaj College of Engineering, Shegaon - 444203, Maharashtra, India
[7]Department of Mechanical Engineering, Saraswati College of Engineering, Kharghar - 410210, Maharashtra, India; baviskardevakant@gmail.com

Abstract

This article provides a comprehensive review of the creation of sustainable biomaterials through Additive Manufacturing (AM). In the manufacturing industry, sustainable biomaterials hold significant promise for enhancing ecological balance and addressing environmental challenges. The initial section of the article defines the principles of sustainability and underscores its relevance for additive manufacturing and biomaterials, stressing the need for eco-friendly products and processes. Following that, it examines various sustainable biomaterials suitable for AM, discussing their applications and properties, including biodegradable polymers and bio-based composites. Next, it addresses the opportunities and challenges associated with the implementation of sustainable biomaterials in additive manufacturing, such as issues with scalability, processing limitations, and material accessibility. Recent advancements and strategies aimed at overcoming these challenges and promoting the widespread adoption of sustainable biomaterials are highlighted. The article wraps up by emphasizing the significance of sustainable biomaterials in additive manufacturing and providing insights into their uses, applications, and future prospects. This resource will be invaluable for researchers and industry experts aiming to foster sustainable development within the biomaterials field and advance environmentally responsible manufacturing practices.

Major Findings: *Additive manufacturing (AM) enables the precise fabrication of sustainable biomaterials, such as biodegradable polymers and bio-based composites, reducing environmental impact. Integration of bio-based materials with AM promotes circular economy practices like waste reduction, recycling, and closed-loop systems. The interdisciplinary synergy between materials science, sustainability, and AM processes is essential for scalable, ethical, and eco-efficient industrial production.*

Keywords: *Additive Manufacturing, Biomaterials, Biomaterial Industry, Nano-Bio Composites, Sustainable Biomaterials*

**Author for correspondence*

1.0 Introduction about Sustainable Biomaterials and Additive Manufacturing (AM)

Sustainability has been an important driver in the advancement of materials and production methods. The use of sustainable biomaterials in additive manufacturing methods has gained popularity due to its potential to alleviate environmental issues[1,2]. For example, biomaterials such as plant-derived cellulose and crustacean shell chitosan are being studied for their renewable and biodegradable qualities[3,4]. Furthermore, proteins such as silk and collagen, along with different biopolymers, are being exploited for their biocompatibility and ability to replicate natural tissue architectures[5,6].

The combination of sustainable biomaterials with additive manufacturing techniques such as Fused Deposition Modelling (FDM), Stereolithography (SLA), and Selective Laser Sintering (SLS) shows great potential for revolutionising a variety of sectors. These additive manufacturing technologies enable the accurate construction of complicated structures from a variety of materials, including biomaterials, therefore facilitating the creation of personalised, sustainable goods while minimising waste[7,8].

The combination of sustainable biomaterials with additive manufacturing has great potential for a variety of applications. In the biomedical area, the capacity to 3D print patient-specific implants, scaffolds for tissue engineering, and medication delivery systems with biomaterials might lead to better patient outcomes and less reliance on traditional, non-sustainable materials[9]. In the consumer goods industry, using sustainable biomaterials in AM-produced products including packaging, home items, and automobile components might help to create a circular economy and lessen manufacturing's environmental impact[10]. However, the effective adoption of sustainable biomaterials in additive manufacturing does not come without hurdles. Material characteristics, processability, and scalability are all important considerations for ensuring the end products' reliability, performance, and cost-effectiveness. Ongoing




Figure 1. Visualizing additive manufacturing: A comprehensive overview of various AM processes.

research and development in this sector aim to address these issues and realise the full potential of the convergence of sustainability and advanced manufacturing[11].

This introduction emphasises the importance of integrating sustainable biomaterials with additive manufacturing, demonstrating its potential to promote innovation and contribute to a more sustainable future. As this discipline evolves, it has the potential to revolutionise the way we design, create, and consume items, ultimately leading to a more ecologically responsible and resource-efficient society.

2.0 Biopolymer-based Sustainable Materials for Additive Manufacturing

The growing interest in environmentally friendly manufacturing solutions has encouraged an increase in research into biopolymers as feedstock materials for Additive Manufacturing (AM) methods[12]. Biopolymers, which are generated from many biological sources such as plants, animals, and microbes, are a type of natural, renewable, and biodegradable polymer[13]. This provides an appealing alternative to traditional petroleum-based polymers, which are infamous for their non-renewable nature and poor degradability[14].A key benefit of biopolymers in additive manufacturing is their inherent sustainability. Unlike synthetic polymers, biopolymers may be made from renewable and frequently waste-derived materials, decreasing reliance on finite fossil fuel reserves[15,16]. Furthermore, many biopolymers demonstrate biodegradability, which enables their breakdown through natural processes and reduces the buildup of plastic waste in the environment.

Several biopolymers have been successfully incorporated into AM processes, including:

1. Polylactic Acid (PLA): PLA is a widely used biopolymer generated from renewable sources including maize, sugarcane, and cassava. It is noted for its good processability, biodegradability, and mechanical qualities, making it appropriate for a number of AM applications, including 3D printing of consumer items, packaging, and medical equipment.
2. Polyhydroxyalkanoates (PHAs): PHAs are a kind of biopolymer generated by bacteria for storing purposes. They have high biocompatibility and biodegradability, making them ideal for biomedical applications such tissue engineering scaffolds and drug delivery systems.
3. Cellulose-based Materials: Cellulose, the most prevalent natural polymer on the planet, may be derived from a variety of plant sources and utilised in AM processes. Cellulose-based materials, particularly nanocellulose and cellulose derivatives, have unique qualities such as high strength, flexibility, and




Figure 2. Exploring the fundamental categories of biodegradable polymers.

printability, opening up possibilities in industries including packaging, electronics, and construction.

4. Chitosan: Chitosan is a biopolymer produced from crustacean shells, specifically prawns and crab. It has antibacterial qualities, is biocompatible, and can form complex structures, making it appropriate for biomedical applications such as wound dressings and tissue engineering.

The effective integration of biopolymers into additive manufacturing demands overcoming various hurdles, such as optimising material characteristics, improving processability, and assuring consistent component quality[17,18]. Current research efforts in this sector are focused on the creation of enhanced biopolymer composites, blends, and modifications to improve the mechanical, thermal, and rheological properties of these materials[19,20]. These improvements are critical for making biopolymers more compatible with various additive manufacturing techniques.

Furthermore, the use of biopolymer-based materials in additive manufacturing can help to achieve the overall objective of a circular economy, in which waste is reduced and materials are reused or recycled. AM can help to build eco-friendly goods and reduce plastic waste by harnessing the sustainability and biodegradability of biopolymers[21,22]. As the area of biopolymer-based sustainable materials for additive manufacturing continues to grow, it has the potential to alter the way we design, make, and consume things, ultimately contributing to a more sustainable and ecologically responsible future.

3.0 Bio-based Nano-Composites: Properties and Applications

The rising emphasis on sustainability and environmental consciousness has fuelled interest in the development of bio-based nanocomposites. These new materials combine the advantages of bio-based polymers with the distinct features of nanoparticles, providing a possible answer to the issues raised by typical petroleum-based composites[23,24].

Bio-based nanocomposites consist of a bio-based polymer matrix, such as polylactic acid (PLA), cellulose, chitosan, or Polyhydroxyalkanoates (PHAs), reinforced with nanoscale fillers or additives[25-27]. These nanomaterials can be natural or manufactured nanoparticles, nanofibers, or nanotubes generated from renewable sources or developed to perform specific functions[28-30].

Incorporating nano-scale fillers into bio-based polymer matrices can significantly improve a variety of material characteristics, including

3.1 Mechanical Properties

The addition of nanofillers such as cellulose nanocrystals, nanoclays, and carbon-based nanoparticles to biodegradable polymer matrix considerably improves the mechanical characteristics of bio-based nanocomposites. These nanoscale reinforcements help to increase tensile strength, flexural strength, impact resistance, stiffness, and toughness[31,32]. This improvement is primarily due to the homogeneous dispersion of nanofillers and strong interfacial contacts with the polymer matrix, which allow for effective stress transmission while limiting polymer chain mobility. The interfacial connection between the biopolymer and nanofillers is critical for obtaining high mechanical performance. Because of these enhanced qualities, bio-based nanocomposites are rapidly being used in structural and load-bearing applications in the automotive, packaging, and construction sectors. Furthermore, their lightweight nature and sustainability make them a possible alternative to conventional petroleum-based composite materials.

3.2 Thermal and Barrier Properties

The addition of nanoscale fillers to bio-based nanocomposites improves their thermal and barrier characteristics significantly. The use of nanofillers such as nanoclays, graphene oxide, or cellulose nanocrystals improves the thermal stability of the polymer matrix by providing a more sinuous channel for heat transmission. This results in delayed thermal deterioration and increased heat resistance, which is critical for packaging and automotive applications. Furthermore, the barrier qualities against gases and moisture are greatly increased, thanks to the production of a tight, layered structure that limits molecular transport. This makes bio-based nanocomposites appropriate for use in food packaging, where preservation and shelf life are crucial. The nanofillers reduce permeability and increase insulation, allowing the composite to function similarly to traditional synthetic materials. Overall, thermal and barrier property increases broaden the

functional range of bio-based polymers, encouraging their use in high-performance, sustainable material applications.

3.3 Biodegradability and Compostability

One of the most notable benefits of bio-based nanocomposites is their capacity to decay naturally in the environment, making them biodegradable and compostable under the right conditions. These materials are largely generated from renewable resources such as starch, Poly Lactic Acid (PLA), or Poly Hydroxy Alkanoates (PHA), and when mixed with natural nanofillers such as nanocellulose or chitosan, they retain or even improve their environmentally beneficial properties. Microbial activity degrades polymer chains into water, carbon dioxide, and biomass. Compostability guarantees that materials degrade within a certain time range in industrial or domestic composting systems without leaving hazardous leftovers[33,34]. The rate of biodegradation varies with environmental circumstances, but the overall environmental effect is substantially lower than that of petroleum-based plastics. These qualities make bio-based nanocomposites very ideal for single-use goods, packaging, and agricultural uses. This aligns with worldwide initiatives to reduce plastic waste and promote a circular, sustainable materials economy.

3.4 Functional Properties

Bio-based nanocomposites have a diverse set of functional features that go beyond mechanical and thermal performance. Depending on the nanofiller used, these materials can have antibacterial, antioxidant, UV-resistant, or flame-retardant properties. For example, the inclusion of silver or zinc oxide nanoparticles can provide antibacterial activity, making them excellent for food packaging, medical equipment, or hygiene items. Similarly, natural extracts or functionalised nanoclays can give antioxidant qualities that aid in the preservation of food or pharmaceuticals. Nanoparticles such as titanium dioxide can be used to provide UV protection, improving product stability and lifetime when exposed to sunlight. In addition, functional qualities like electrical conductivity or magnetic responsiveness may be tuned for use in sensors, smart packaging, or flexible electronics. Bio-based nanocomposites are a very adaptable class of materials because of their capacity to fine-tune these capabilities using green, sustainable inputs. They bridge the gap between environmental responsibility and enhanced material performance.

The applications of bio-based nano-composites span a wide range of industries, including:

1. Packaging: Bio-based nanocomposites with improved barrier qualities and mechanical strength can be utilised to create environmentally friendly and biodegradable packaging for food, cosmetics, and consumer products.
2. Biomedical: Bio-based nano-composites may be used to make tissue engineering scaffolds, wound dressings, and drug delivery systems, taking advantage of their biocompatibility and biodegradability.
3. Electronics and Energy: Bio-based nano-composites, such as those incorporating conductive nanofillers, have potential uses in the creation of flexible electronics, energy storage devices, and sensors.
4. Construction and automobiles: Bio-based nano-composites have increased thermal and mechanical qualities, making them appropriate for application in building materials, insulation, and automotive components.

Figure 3 illustrates how the synergistic combination of renewable bio-based polymers and functional nanomaterials has the potential to drive the development of sustainable, high-performance, and environmentally friendly materials for a variety of applications.

4.0 Challenges and Opportunities in Using Sustainable Biomaterials for Additive Manufacturing

The combination of sustainable biomaterials with Additive Manufacturing (AM) technology poses both obstacles and possibilities in the pursuit of more environmentally responsible manufacturing solutions. As researchers and industry stakeholders investigate the possibilities of this junction, many crucial aspects must be addressed to unlock the full potential of sustainable biomaterials in AM processes, as shown in Figure 4.

4.1 Challenges

Despite its potential, integrating Additive Manufacturing (AM) into biomaterial production




Figure 3. Visualizing the sustainable lifecycle of bio-based packaging materials[3].



Figure 4. Challenges and opportunities in additive manufacturing with biomaterials.

presents various hurdles. The intricacy of processing bio-based materials, which are frequently sensitive to heat and moisture, necessitates careful control over printing settings. Achieving constant quality and reproducibility in printed items is another key issue. Furthermore, many bio-based materials have low mechanical strength and endurance, limiting their use in load-bearing situations. Printer compatibility with biodegradable feedstocks also presents challenges. Addressing these difficulties needs breakthroughs in material research, printer design, and post-processing procedures to fully harness the potential of sustainable AM technology.

4.1.1 Material Properties

Biomaterials' processability in additive manufacturing is determined by their thermal behaviour, rheological qualities, and stability. Many bio-based polymers, such as PLA and PHA, provide promising results because to their thermoplastic nature, but others may deteriorate at high temperatures utilised in AM processes like as FDM or SLS. Controlling variables like as viscosity, flow rate, and layer adhesion is critical to effective manufacturing. Changes, such as blending or adding plasticisers, are frequently required to enhance printability. Understanding and optimising the link between material qualities and processing parameters is critical for achieving consistent and high-quality bio-printed components.

4.1.2 Scalability and Cost-Effectiveness

Scaling up additive manufacturing with biomaterials involves both economic and technological challenges. While 3D printing provides customisation and waste reduction, it frequently falls behind traditional manufacturing in terms of speed and production volume. Bio-based feedstocks are expensive and scarce, which raises overall costs. Equipment maintenance, material waste from trial-and-error runs, and energy use all have an impact on cost-effectiveness. To accomplish scalable, cost-effective manufacturing, improvements in printing speed, multi-head systems, and automated post-processing are required. Furthermore, lowering the cost of bio-based materials through industrial-scale biopolymer synthesis might help make sustainable AM more feasible for mass manufacturing.

4.1.3 Regulatory and Certification Challenges

Biomaterial-based additive manufacturing must negotiate complicated regulatory environments to assure product safety and performance. Materials used in the medical, culinary, and packaging sectors must meet health and safety criteria, which include biocompatibility and biodegradability certifications. However, existing rules are frequently tailored for traditional materials and methods, generating uncertainty for innovative AM techniques. The lack of standardised testing procedures and certification processes for 3D-printed bio-based items limits their commercialisation. Collaboration between academics, producers, and regulatory agencies is critical for developing clear norms and frameworks. Addressing these difficulties is critical for building customer trust and ensuring the appropriate use of sustainable AM technology.

4.2 Opportunities

4.2.1 Circular Economy Integration

Biomaterial additive manufacturing promotes material reuse and waste minimisation, which aligns with circular economy ideals. Bio-based polymers generated from renewable sources may be recycled or biodegraded, which reduces environmental effect. AM provides exact material consumption, avoiding waste during production. This technique also enables localised production, which reduces transportation emissions. Integrating additive manufacturing into circular systems improves sustainability by closing material loops, promoting responsible consumption, and fostering innovation in eco-friendly product design and end-of-life solutions.

4.2.2 Customization and Personalization

Additive manufacturing excels in creating customised and personalised items, particularly when paired with sustainable biomaterials. It enables exact control over form, size, and material distribution, resulting in bespoke solutions for healthcare, consumer items, and wearables. For example, biodegradable materials may be used to construct patient-specific implants and prosthesis, assuring both performance and environmental advantages. This versatility allows for small-batch, on-demand production, which reduces inventory waste and promotes sustainable consumption without compromising individual demands or product quality

4.2.3 Biomedical Applications

Additive manufacturing has transformed biomedical applications by utilising biocompatible and biodegradable materials. It permits the creation of bespoke implants, tissue scaffolds, and medication delivery systems based on unique patient anatomy. Using natural polymers like PLA, gelatin, or chitosan improves biological compatibility while being sustainable. These advances lower surgical risks and encourage speedier recovery. The combination of AM and biomaterials has transformational promise in regenerative medicine, prostheses, and personalised healthcare solutions.

4.2.4 Innovative Material Development

The advancement of additive manufacturing in biomaterials has accelerated the creation of novel, high-performance materials. Researchers are developing composites by combining natural fibres, nanomaterials, or bio-fillers with biodegradable polymers to increase strength, flexibility, and usefulness[35-37]. These materials satisfy specified performance requirements while staying environmentally friendly. Advances in bio-resins, responsive materials, and multifunctional biopolymers are broadening the scope of sustainable 3D printing across sectors. These breakthroughs drive the next generation of green, adaptive industrial solutions.

By solving the problems and capitalising on the possibilities provided by sustainable biomaterials in additive manufacturing, the industry can work together to create a more ecologically responsible and resource-efficient future[38,39]. Continuous research, cooperation, and the development of comprehensive solutions will be critical in realising the full potential of this junction of sustainability and advanced manufacturing[40-42].

5.0 Modern Developments and Insights in Biomaterials using Additive Manufacturing Technologies

Rapid breakthroughs in Additive Manufacturing (AM) technology have opened up new horizons in biomaterials, allowing for the development of unique and customisable solutions for a wide range of applications. Researchers and industry actors have actively investigated the synergies between biomaterials and AM, resulting in a variety of current advancements and insights.

5.1 Bioprinting for Tissue Engineering

Bioprinting is a significant use of biomaterials in additive manufacturing, allowing the fabrication of functional tissue constructions by mixing living cells, bio-based materials, and growth hormones. Significant progress has been achieved in bioink formulation utilising natural ingredients such as collagen, gelatin, alginate, and cellulose, all of which enhance cell survival and tissue regeneration. Innovations in multi-material printing and the effective inclusion of vascular systems have increased the capacity to construct complex, layered tissues that nearly imitate the original extracellular matrix.

5.2 Personalized Implants and Prosthetics

Additive manufacturing, when paired with patient-specific biomaterials, has revolutionised the fabrication of personalised implants and prosthesis[43]. Materials such as titanium alloys, calcium phosphate-based ceramics, and biodegradable polymers can be 3D printed to create custom-fitted bone and joint implants that are tailored to an individual's anatomical structure and medical needs. Furthermore, the combination of biomaterials and smart technology has allowed the development of intelligent implants capable of real-time monitoring. These smart solutions improve post-operative care and lead to better recovery and long-term patient outcomes.

5.3 Wound Healing and Drug Delivery

Wound dressings and medication delivery systems made from sustainable biomaterials such as chitosan, alginate, and gelatin are commonly produced via additive manufacturing. These natural materials are highly biocompatible and may be developed to promote tissue regeneration, avoid infections, and maintain an ideal healing environment. Wound dressings may be adapted to particular wound types using 3D printing, and drug delivery systems can be customised for controlled release, personalised dosage, and focused therapy. This strategy improves treatment efficiency and patient care in a sustainable and creative way.

5.4 Biobased Composites and Nanocomposites

The combination of biomaterials and nanomaterials has paved the way for the development of high-performance bio-based composites and nanocomposites suitable for a variety of applications. Researchers have concentrated on reinforcing biopolymer matrices such as PLA, PHAs, and chitosan with natural fibres, cellulose nanocrystals, and other renewable nanomaterials to greatly increase mechanical strength, thermal stability, and overall usefulness. These eco-friendly composites exhibit tremendous promise in areas such as packaging, automotive, and construction, providing a sustainable alternative to traditional, petroleum-based materials without losing performance.

5.5 Recycling and Upcycling of Biomaterials

In keeping with circular economy concepts, continuing research is on recycling and upcycling biomaterials used in additive manufacturing. Innovative technologies, such as chemical and enzymatic recycling of biopolymers, have been developed to recover resources while reducing environmental effect[44]. By reintegrating these recovered biomaterials into the AM process, closed-loop manufacturing systems may be established. This strategy not only eliminates material waste, but also improves the overall sustainability of bio-based products, supporting long-term environmental and economic goals[45-47]. These recent breakthroughs and insights in biomaterials and additive manufacturing indicate substantial progress in utilizing biomaterials' unique features and sustainability to address a variety of difficulties[48-50]. As research and innovation in this sector continues, the combination of biomaterials and AM technologies is set to generate revolutionary changes in different industries, paving the way for a more sustainable and ecologically conscious future[51,52].

6.0 Conclusion

The fusion of biomaterials with additive manufacturing marks a transformative shift towards more ethical and sustainable production practices. By harnessing the renewable and biodegradable qualities of bio-based materials alongside the precision and material-saving advantages of additive technologies, industries can significantly reduce their environmental footprint. The success of this integration depends on the careful selection and optimization of biomaterials, refinement of AM processes to suit their unique characteristics, and strong collaboration across fields such as materials science, engineering, and sustainability. Adopting circular

economy strategies including recycling, waste reduction, and closed-loop systems further strengthens the environmental benefits of this approach. The adaptability of combining biomaterials with additive manufacturing opens up possibilities in a wide range of sectors, from personalized healthcare solutions to eco-friendly building materials. As specialized applications continue to drive innovation, this interdisciplinary effort is gradually reshaping manufacturing into a more circular, resource-efficient model. Ultimately, additive manufacturing with biomaterials holds great promise for aligning industrial production with global sustainability initiatives, fostering ethical design, responsible production, and mindful consumption across diverse industries.

7.0 Declaration

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

8.0 References

1. Arif ZU, Khalid MY, Noroozi R, Hossain M, Shi HH, Tariq A, Umer R. Additive manufacturing of sustainable biomaterials for biomedical applications. Asian J Pharm Sci. 2023; 18(3):100812. https://doi.org/10.1016/j.ajps.2023.100812 PMid:37274921 PMCid:PMC10238852.
2. Okolie O. Kumar A, Edwards C, Lawton LA, Oke A, McDonald S, Thakur VK, Njuguna J. Bio-based sustainable polymers and materials: From processing to biodegradation. J Compos Sci. 2023; 7:213. https://doi.org/10.3390/jcs7060213
3. Reichert CL, Bugnicourt E, Coltelli, MB, Cinelli P, Lazzeri A, Canesi I, Braca F, Martínez BM, Alonso R, Agostinis L, *et al.* Bio-based packaging materials, modifications, industrial applications and sustainability. Polymers. 2020; 12:1558. https://doi.org/10.3390/polym12071558 PMid:32674366 PMCid:PMC7407213.
4. Espinosa E, *et al.* Cellulose-based materials in additive manufacturing. Materials. 2019; 12(11):1843.
5. Sun J, *et al.* A comprehensive review on chitosan-based materials used in 3D printing and tissue engineering. Carbohydrate Polymers. 2021; 266:118103.
6. Kundu J, *et al.* Silk fibroin biomaterials for tissue regenerative engineering. Biomaterials. 2013; 34(38):8950-8967.
7. Chaporkar MS, Misal K, Bhoyar A, Dhole RK. Design and development of constrain based XY flexural mechanism. In: Pawar P, Ronge B, Balasubramaniam R, Vibhute A, Apte S, editors. Techno-Societal. Springer, Cham; 2018. https://doi.org/10.1007/978-3-030-16962-6_27
8. Bartolo P, *et al.* 3D printing of sustainable bioplastics: A review. Virtual and Physical Prototyping. 2020; 15.3:261-276.
9. Dutta D, *et al.* A review on stereolithography and its applications in biomedical engineering. Materials Science and Engineering: C. 2020; 107:110267. https://doi.org/10.1016/j.msec.2019.110267 PMid:31761248 PMCid:PMC6907012.
10. Vinod M, Kumar CA, Sollapur SB, *et al.*, Study on low-velocity impact performance of chemical treated flax fibre-reinforced aluminium 6082 laminates. J Inst Eng India Ser D. 2024. https://doi.org/10.1007/s40033-024-00657-0
11. Gebisa A, *et al.* Challenges and opportunities of sustainable biomaterials in additive manufacturing: A review. J Clean Prod. 2021; 292:125963.
12. Chiulan I, *et al.* Additive manufacturing of polymeric structures containing biopolymer: A review. J Appl Polym Sci. 2017; 134(16):44667.
13. Reddy N, *et al.* Biopolymers and biopolymer-based nanocomposites: Current status and future perspectives. Progress in Materials Science. 2014; 1-48.
14. Narancic T, *et al.* Biodegradable plastic blends create new possibilities for end-of-life management of plastics but they are not a panacea for plastic pollution. Environmental Sciences Europe. 2021; 33(1):66.
15. Nampoothiri K, Madhavan, *et al.* Biodegradable and compostable alternatives to conventional plastics. Environmental Science and Pollution Research. 2018; 25(8):7291-7304.
16. Sollapur SB, Sharath, PC, Waghmare P. Applications of additive manufacturing in biomedical and sports industry. In: Rajendrachari S, editors. Practical implementations of additive manufacturing technologies. Materials horizons: From nature to nanomaterials. Singapore: Springer; 2023. https://doi.org/10.1007/978-981-99-5949-5_13
17 Goh GD, *et al.* Advances in biopolymer-based additive manufacturing materials. Advanced Science. 2020; 7(11):1903366.
18 Ning F, *et al.* Development of biopolymer-based materials for additive manufacturing: A review. Rapid Prototyp J. 2021; 27(4):893-907
19. Shrishail SB, Suryawanshi SR, Mhatre M, Dond DK, Chate G, Bhowmik A. Predictive modeling of tool life in

turning using ANN-taguchi hybridization. TSWJ. 2024. https://doi.org/10.1155/2024/9129669
20. John, ML, *et al.* Bio-based polymers and their nanocomposites: Promising green materials for a sustainable future. Environmental Science and Pollution Research. 2019; 26(7):6290-6316.
21. Espinosa E, *et al*. Cellulose-based materials in additive manufacturing. Materials. 2019; 12(11):1843.
22. Sollapur SB, Dakhole MY, Suryawanshi, SR, Kumar, VV, Bakar SA. Optimizing bionic prosthetic finger 3D topology design and comprehensive testing of fully compliant mechanisms. Int J Integr Eng. 2024; 16(6):285-293. https://doi.org/10.30880/ijie.2024.16.06.027
23. Pratik W. Development and performance investigation of solar concrete collector at different climatic conditions. IJEMS. https://doi.org/10.56042/ijems.v30i2.1384
24. Hopkinson N, *et al*. The additive manufacturing process and its environmental sustainability. Int J Adv Manuf Tech. 2021; 114(1-2):63-80
25 Ngo T-P, *et al.* Recycled biomaterials in additive manufacturing: A review. Polymers. 2021; 13(11):1780.
26 Ozbolat IT, Huang Y. Additive manufacturing: Scientific and technological challenges, market uptake and opportunities. Materials Today. 2018; 21(1):22-37. https://doi.org/10.1016/j.mattod.2017.07.001
27 Ngo T-P, *et al*. Biodegradable materials for 3D printing. Annual Review of Chemical and Biomolecular Engineering. 2020; 11:403-426.
28. Saravanan D, *et al*. Tribological properties of filler and green filler reinforced polymer composites. Materials Today: Proceedings. 2022; 50:2065-2072. https://doi.org/10.1016/j.matpr.2021.09.414
29. Waghmare PM, Bedmutha PG. Investigation of effect of hybridization and layering patterns on mechanical properties of banana and kenaf fibers reinforced epoxy biocomposite. Materials Today: Proceedings. 2021; 46:3220-3224. https://doi.org/10.1016/j.matpr.2020.11.194
30. Shinde T, *et al*. Fatigue analysis of alloy wheel using cornering fatigue test and its weight optimization. Proceedings. 2022; 62:1470-1474. https://doi.org/10.1016/j.matpr.2022.02.023
31. Chate GR, *et al.* Ceramic material coatings: Emerging future applications. Advanced Ceramic Coatings for Emerging Applications. Elsevier; 2023. p. 3-17. https://doi.org/10.1016/B978-0-323-99624-2.00007-3
32. Patil MS, Deshmukh SP. Position estimator algorithm implementation on precision applications. Proceedings. 2020; 24:333-342. https://doi.org/10.1016/j.matpr.2020.04.283
33. Agrawal R, *et al.* The role of additive manufacturing in the sustainable consumer goods industry. IJSM. 2021; 1(1-2):47-61.
34. Sollapur SB, *et al.* Experimental investigation of high precision XY mechanism. IJMET. 2018; 9(5):43-50.
35. Mouser VHM, Sander CG. The use of collagen-based biomaterials in tissue engineering applications. J Tissue Eng Regen Med. 2020; 14(12):1705-1724.
36. Baviskar DD, Rao AS, Sollapur S, *et al.* Development and testing of XY stage compliant mechanism. Int J Interact Des Manuf. 2023. https://doi.org/10.1007/s12008-023-01612-1
37. Waghmare P. Design and experimental investigation of XY compliant mechanism for precision applications. ECS Transactions. 2022. 107(1). https://doi.org/10.1149/10701.4967ecst https://doi.org/10.1149/10701.4967ecst
38. Vinod M, Kumar CA,Sollapur SB. *et al*., Study on fabrication and mechanical performance of flax fibre-reinforced aluminium 6082 laminates. J Inst Eng India Ser D. 2023; 105:1905-1916. https://doi.org/10.1007/s40033-023-00605-4
39. Gowda V, Nagaraja C, Yogesha KB *et al*. Study on structural behavior of HVOF-Sprayed NiCr/Mo Coating. J Inst Eng India Ser. D. 2024; 105:1961-1970. https://doi.org/10.1007/s40033-024-00641-8
40. Waghmare PM, Sollapur SB, Wange SM. Concrete solar collector. Advances in smart grid and renewable energy: Proceedings of ETAEERE-2016. Singapore: Springer; 2018. https://doi.org/10.1007/978-981-10-4286-7_46
41. Raut PP, Rao AS, Sollapur S, *et al*. Investigation on the development and building of a voice coil actuator-driven XY micro-motion stage with dual-range capabilities. Int J Interact Des Manuf. 2023; 18:4397-4408. https://doi.org/10.1007/s12008-023-01665-2
42. Shah AA, *et al.* Biodegradation of polymeric materials: A review. Materials Today: Proceedings. 2018; 5(1):552-558.
43. Nagaraj C, Dutt KM, Manjunath GK, Sharath PC, Sollapur SB, B, RBK, Arunkumar DT. Effect of multidirectional forging on grain structure and mechanical properties of hypereutectic Al-20%Si alloys with added refiners and modifiers. Canadian Metallurgical Quarterly. 2025; 64(3):1-15. https://doi.org/10.1080/00084433.2024.2413245
44. Chikkangoudar RN, Patil C, Panchal N. *et al.* Investigating joint-free mechanical systems with PLA and ABS materials using the fuse deposition modelling method. J Inst Eng India Ser. D. 2024. https://doi.org/10.1007/s40033-024-00659-y

45. Sollapur SB, Waghmare PM, Patil M, Deshmukh S. Design and experimental testing of XY flexure mechanism. JESTEC. 2021; 16(2):1416-1425.
46. Shinde T, Raut S, Atpadkar A, Nimbalkar P, Rathod M. Design and development of high-precision scanning flexural mechanism using PID. In: Sachdeva A, Goyal KK, Garg, RK, davim, JP. (eds) Recent advances in operations management and optimization. CPIE 2023. Lecture Notes in mechanical engineering. Singapore: Springer; 2024. https://doi.org/10.1007/978-981-99-7445-0_4
47. Ray SS, Chatterjee S. Bio-nanocomposites: A review on their properties and applications. J Compos Sci. 2018; 2(2):35
48. Raut PP, Rao AS. Design of flexural bearings in experimental analysis and PID control of a voice coil actuator. In: Kumar A, Iyer G, Desai U, Kumar A, editors. Advances in design and automation. ICFAMMT 2024. Lecture Notes in mechanical engineering. Springer: Singapore; 2025. p. 49-57. https://doi.org/10.1007/978-981-97-5621-6_4
49. Arunadevi M, Veeresha G, Kharche AW, *et al*. Enhancing surface quality of metal parts manufactured via LPBF: ANN classifier and bayesian learning approach. Int J Interact Des Manuf 2024; 18:4093-4101. https://doi.org/10.1007/s12008-024-01942-8
50. Thompson DN, *et al*. Sustainable biomaterials for additive manufacturing: Opportunities and challenges. J Clean Prod. 2019; 215:960-972.
51. Baviskar DD, Rao AS, Raut PP. Designing a piezo-actuated four-bar motion amplification mechanism for enhanced compliance. In: Kumar A, Iyer G, Desai U, Kumar A, editors. Advances in design and automation. ICFAMMT 2024. Lecture notes in mechanical engineering. Singapore: Springer; 2025. p. 95-105 https://doi.org/10.1007/978-981-97-5621-6_8
52. Sun J, *et al*. A comprehensive review on chitosan-based materials used in 3D printing and tissue engineering. Carbohydrate Polymers. 2021; 266:118103.