Journal of Mines, Metals and Fuels, *73(8): 2291-2306; 2025. DOI: 10.18311/jmmf/2025/49420*

Print ISSN : 0022-2755

Journal of Mines, Metals and Fuels

**Contents available at:** *www.informaticsjournals.co.in/index.php/jmmf*

# Overview of Drop Shafts for Storm and Waste Water Management

**S. G. Joshi[1*], Shyam Shukla[2] and Virendra Bhojwani[1]**

[1]*Department of Mechanical Engineering MIT Art, Design and Technology University, Rajbaugh Loni Kalbhor, Pune - 412201, Maharashtra, India; sgjoshi059@gmail.com*

[2]*Department of Civil Engineering, MIT Academy of Engineering, Pune - 412105, Maharashtra, India*

## Abstract

*Urban rivers often receive a mixture of storm water, treated waste water, and occasionally, partially treated sewage-posing a significant challenge to water quality management. Among the engineering solutions employed, drop shafts play a pivotal role in enabling controlled vertical conveyance of water while minimizing energy loss, turbulence, and air entrainment. This paper presents a comprehensive overview of drop shaft hydraulics, encompassing design principles, operational mechanisms, and recent advancements in Computational Fluid Dynamics (CFD) modeling. Various drop shaft configurations-including tangential vortex, plunge pool, and helicoidal designs-are critically analyzed for their energy dissipation efficiency and air core formation. Insights are drawn from real-world implementations such as the Thames Tideway Tunnel, Chicago's Deep Tunnel, and Sao Paulo's helicoidal system. Emphasis is placed on turbulence modeling approaches (RANS, LES, and DNS) and the integration of CFD with physical scale models. The study includes a case-specific CFD and experimental validation of drop shaft parameters, emphasizing cost-effective evaluation techniques. Recommendations promote AI-based design optimization, modular prefabrication, and climate-resilient approaches for future urban water infrastructure.*

**Major Findings:** *The study highlights that vortex drop shafts are the most efficient in energy dissipation and air entrainment control, while maintaining moderate maintenance requirements. Integration of CFD modeling with experimental validation proved crucial for optimizing drop shaft designs. Future advancements recommend incorporating AI for automated design optimization, modular prefabrication for construction efficiency, and climate-resilient approaches for long-term sustainability.*

**Keywords:** *CFD Modeling, Drop Shaft Design, Energy Dissipation, Helicoidal Shaft, Stormwater Management, Tangential Vortex, Turbulence Modeling*

## 1.0 Introduction

Stormwater management plays a critical role in modern urban infrastructure, ensuring the safe conveyance and disposal of rainwater to prevent flooding, water logging, and structural damage to sewer systems. One of the primary challenges in stormwater management is the controlled transportation of water from higher elevations to lower elevations while minimizing turbulence, energy dissipation losses, and structural damage. This is where drop shafts come into play.

Drop shafts are vertical conduits designed to transfer water or wastewater between different elevations in a controlled manner. Their primary function is to dissipate the energy of falling water to prevent excessive turbulence and air entrainment, which can cause hydraulic inefficiencies, noise, vibration, and cavitations. Various designs of drop shafts exist, each catering to different flow rates, site constraints, and structural considerations. Urban water infrastructure grapples with the intricate challenge of managing combined sewer

**Author for correspondence*

overflows, stormwater runoff, and wastewater discharges, necessitating innovative engineering solutions that can effectively mitigate environmental impacts and safeguard public health[1]. Drop shafts, as integral components of urban drainage systems, facilitate the controlled conveyance of water from higher elevations to lower levels, often into deep tunnels or large interceptors, thereby minimizing energy dissipation, reducing turbulence, and mitigating air entrainment[2]. The effective design and operation of drop shafts are thus paramount in ensuring the hydraulic efficiency and structural integrity of urban water management systems, especially in the face of increasing urbanization and climate change impacts. This paper delves into the hydraulic principles governing drop shaft operation, explores various design configurations, and examines the application of computational fluid dynamics in optimizing drop shaft performance. Urban water infrastructure grapples with the intricate challenge of managing combined sewer overflows, stormwater runoff, and wastewater discharges, necessitating innovative engineering solutions that can effectively mitigate environmental impacts and safeguard public health[1]. Drop shafts, as integral components of urban drainage systems, facilitate the controlled conveyance of water from higher elevations to lower levels, often into deep tunnels or large interceptors, thereby minimizing energy dissipation, reducing turbulence, and mitigating air entrainment[2]. The effective design and operation of drop shafts are thus paramount in ensuring the hydraulic efficiency and structural integrity of urban water management systems, especially in the face of increasing urbanization and climate change impacts. This paper delves into the hydraulic principles governing drop shaft operation, explores various design configurations, and examines the application of computational fluid dynamics in optimizing drop shaft performance. The design of drop shafts hinges on a comprehensive understanding of fluid mechanics, encompassing energy dissipation, air-water interactions, and structural stability. Different design configurations, such as tangential vortex, plunge pool, and helicoidal systems, offer varying degrees of energy dissipation and air entrainment control[3]. Tangential vortex drop shafts induce a swirling motion that promotes energy dissipation through increased shear stresses and turbulence[4]. Plunge pool drop shafts utilize a pool of water at the base of the shaft to dissipate energy through impact and wave action[5]. Helicoidal drop shafts, characterized by a spiral-shaped conduit, encourage a gradual reduction in flow velocity and minimize air entrainment through a controlled descent[6]. Selecting an appropriate configuration necessitates a holistic evaluation of site-specific constraints, design flow rates, and the desired level of energy dissipation[7]. Operational mechanisms are equally critical, demanding careful consideration of inlet geometry, shaft diameter, and outlet conditions to optimize hydraulic performance and minimize operational issues such as clogging and excessive air entrainment. The implementation of intelligent building designs, though promising, may encounter operational challenges, highlighting the importance of robust design and management strategies in urban water infrastructure[8]. The utilization of numerical simulation can aid in determining the hydraulic characteristics of the flow within the damper, thereby optimizing its performance[9]. Computational fluid dynamics modeling has emerged as a powerful tool for simulating and analyzing the complex flow dynamics within drop shafts[10]. Turbulence modeling plays a pivotal role in accurately capturing the intricate flow phenomena that govern energy dissipation and air-water interactions[11]. Reynolds-averaged Navier-stokes models, such as the k-ε and k-ω models, provide a computationally efficient approach for simulating turbulent flows, albeit with limitations in capturing complex flow features such as large-scale eddies and flow separation. Large Eddy simulation, on the other hand, offers a more detailed representation of turbulence by explicitly resolving large-scale eddies while modeling the smaller scales, albeit at a higher computational cost. Direct numerical simulation, the most computationally intensive approach, resolves all scales of turbulence, providing the most accurate representation of the flow field. Selecting an appropriate turbulence model hinges on a trade-off between accuracy and computational cost, tailored to the specific objectives of the analysis. The accuracy of CFD simulations must be rigorously validated through experimental data, typically obtained from physical scale models. Integrating CFD with physical scale models enables a comprehensive evaluation of drop shaft performance, providing valuable insights for design optimization and risk assessment[12]. It is crucial for effective flood risk management that hydrodynamic models produce accurate predictions[13]. When modeling urban areas it is important to resolve complex flow paths[14]. This is achieved by using coupled 1D and 2D

models[15]. Several large-scale urban water infrastructure projects have successfully incorporated drop shafts as key components of their drainage systems. The Thames Tideway Tunnel in London utilizes drop shafts to convey combined sewer overflows into a deep tunnel, mitigating discharges into the River Thames[16]. Chicago's Deep Tunnel, also known as the Tunnel and Reservoir Plan, employs a network of drop shafts to capture and store stormwater runoff, reducing flooding and improving water quality in the Chicago River. Sao Paulo's helicoidal system incorporates helicoidal drop shafts to minimize air entrainment and energy dissipation, optimizing the performance of the city's drainage system. Analyzing these real-world implementations provides valuable insights into the design, operation, and maintenance of drop shafts in diverse urban environments. Numerical computer modelling has been proven to be an invaluable tool in the assessment of water supply and drainage for buildings. Numerical models can also be applied to sanitation systems in less developed countries so that similar benefits in both efficiency and cost reductions can be achieved[17]. The future of drop shaft design lies in embracing innovative technologies and approaches to enhance performance, sustainability, and resilience. Artificial intelligence-based design optimization can be employed to automatically generate and evaluate a multitude of design alternatives, identifying optimal configurations that meet specific performance criteria[18]. Modular prefabrication offers the potential to accelerate construction timelines, reduce costs, and improve quality control through off-site manufacturing and on-site assembly. Incorporating climate-resilient design principles is crucial to ensure the long-term performance of drop shafts under changing climatic conditions, such as increased rainfall intensity and frequency[19]. Sustainable urban drainage systems have gained increasing public interest in recent years, as a result of their positive effects on water quality and quantity problems[20,21].

## 1.1 Importance of Drop Shafts in Urban Drainage Systems

Urban environments require robust drainage systems to manage stormwater efficiently, especially with increasing urbanization and climate change-induced extreme weather events. Traditional open-channel methods for water transportation are often impractical in densely populated areas, necessitating underground systems that include drop shafts.

Drop shafts serve several critical purposes in urban drainage systems:

1. Energy dissipation: They reduce the velocity of water falling from height, preventing excessive turbulence and structural wear on downstream tunnels.
2. Air entrainment control: A properly designed drop shaft minimizes air entrainment, which can cause pressurization issues and pipe damage.
3. Space efficiency: Unlike open channels, drop shafts occupy minimal surface space, making them ideal for densely populated urban areas.
4. Environmental benefits: By facilitating controlled flow, drop shafts help prevent erosion, sediment deposition, and downstream flooding.

## 1.2 Historical Evolution of Drop Shaft Designs

The concept of vertical shafts for water conveyance has existed for centuries, dating back to ancient Roman aqueducts and Persian qanats. However, modern drop shaft designs have significantly evolved with advances in hydraulic engineering, Computational Fluid Dynamics (CFD), and materials science.

Early drop shafts were simple vertical conduits that relied on gravity to transport water downward. However, these designs often led to excessive turbulence, cavitations, and maintenance challenges. Over time, engineers developed more sophisticated drop shaft designs that incorporate vortex motion, energy dissipation chambers, and air release mechanisms to improve efficiency and longevity.

Notable advancements in drop shaft technology include:

1. Mid-20$^{th}$ century: Introduction of basic baffle and cascade drop shafts to control energy dissipation.
2. Late 20$^{th}$ century: Development of vortex drop shafts to minimize air entrainment and turbulence.
3. 21$^{st}$ century: Implementation of CFD simulations and numerical modeling to optimize drop shaft design and performance.

## 1.3 Classification of Drop Shafts

Drop shafts can be classified based on their design and functional characteristics. The major types include:

### 1.3.1 Simple Drop Shaft

A simple drop shaft is a basic vertical conduit commonly employed in systems with low-flow requirements where minimal energy dissipation is needed. It allows water to descend freely into a lower chamber, typically forming a free jet that dissipates energy upon impact with the bottom pool. Although structurally uncomplicated and cost-effective, this design becomes inefficient at higher flow rates due to significant turbulence and potential cavitation. As illustrated in the Figures 1 and 2, both the "Simple Drop Structure" and the "Free Jet Drop Structure" operate on the principle of gravity-driven vertical descent, directing water into a base chamber where energy is naturally dispersed.





**Figure 1.** Simple drop structure.





**Figure 2.** Free jet drop structure.

### 1.3.2 Plunge Pool Drop Shaft

The plunge pool drop shaft is designed for scenarios involving high-energy wastewater flows. In this configuration, water descends vertically through a deep shaft and directly enters a pool located at the base, known as the Deaeration chamber. This pool acts as an energy dissipation zone, effectively managing the turbulence caused by the falling water. Such structures are particularly effective for deep shaft systems where significant vertical drops occur. However, due to the intense hydraulic impact at the base, these shafts require robust structural reinforcement to withstand the resulting forces and prevent damage over time.

### 1.3.3 Tangential Inlet Vortex Drop Shaft

In a tangential inlet vortex drop shaft, wastewater is introduced into the structure at a tangent, inducing a swirling motion or controlled vortex within the shaft. This design facilitates the gradual and spiral descent of flow, which significantly reduces air entrainment and the formation of turbulent splashes. The vortex action





**Figure 3.** Plunge pool drop shaft.





**Figure 4.** Standalone vortex insert diagram.

effectively manages kinetic energy, enhancing the overall energy dissipation before the water reaches the bottom chamber. This mechanism not only improves flow stability but also minimizes structural wear and improves the efficiency of deep shaft systems, as shown in Figure 4. One of the most efficient designs for high-flow stormwater applications is as shown in Figure 5.

### *1.3.4 Plunge with Deaeration Chamber*

A plunge with Deaeration chamber system integrates a plunge pool with an air release chamber to effectively minimize the entrapment of air within the flow. It typically consists of a drop shaft and an impact cup, designed to dissipate energy and release trapped air before the fluid moves to the discharge conduit. This configuration is especially valuable in scenarios where air entrainment poses a significant operational challenge as shown in Figure 6.

In addition, Flight Sewers and Inclined Drop Shafts are alternative structures used to manage vertical or inclined flow drops in sewer systems. Flight Sewers utilize a series of steps to control the descent of water, while inclined drop shafts allow water to travel along a sloped conduit, reducing free fall and helping to manage velocity and air entrainment effectively.

### *1.3.5 Vortex Insert Drop Shaft*

The Vortex Insert Drop Shaft system utilizes a prefabricated vortex insert strategically positioned inside



**Figure 5.** Spiral vortex.





**Figure 6.** Plunge with deaeration chamber.

the shaft to improve energy dissipation during water descent. This design promotes effective flow control and reduces hydraulic stress within the system. As a modular and economically viable solution, it is particularly suited for storm water management applications, providing flexibility and ease of installation in various infrastructure projects as shown in Figure 7.




**Figure 7.** Vortex drop structure.

### *1.3.6 Helicoidal Drop Shaft*

The Helicoidal Drop Shaft is an advanced hydraulic structure designed to optimize energy dissipation as water descends through a spiral path as presented in Figure 8. Its helicoidal geometry ensures a gradual reduction in flow velocity, which helps in controlling turbulence and reducing structural stress. This design is particularly beneficial for minimizing the overall impact on surrounding infrastructure while efficiently managing vertical water drops in drainage and sewer systems.

### *1.3.7 Baffle (Cascade) Drop Shaft*

The Baffle (Cascade) Drop Shaft is designed with a sequence of internal baffles or steps that enable a controlled and gradual dissipation of energy as water flows downward. This configuration helps in reducing the velocity of descending water, thereby minimizing erosion and structural wear. Such systems are particularly well-suited for wastewater treatment facilities, where effective energy management and flow control are essential for system longevity and efficiency.

## 1.4 Challenges and Considerations in Drop Shaft Design

The selection and design of a drop shaft depend on multiple factors, including flow conditions, site constraints, construction feasibility, availability of suitable construction equipment and maintenance requirements. Key challenges in drop shaft design include:

### *1.4.1 Energy Dissipation Efficiency*

1. High-velocity flows can generate significant kinetic energy, requiring effective dissipation mechanisms.
2. Insufficient energy dissipation can lead to erosion, structural damage, and downstream turbulence.




**Figure 8.** Helicoidal drop structure.




**Figure 9.** Baffle structure.

### *1.4.2 Air Entrainment*

1. Rapidly falling water can trap air bubbles, leading to pressurization and potential damage to downstream pipes.
2. Excessive air entrainment can reduce hydraulic efficiency and increase maintenance costs.

### *1.4.3 Sediment and Debris Accumulation*

1. Drop shafts in storm water systems often carry sediment, debris, and organic matter.
2. Proper design must incorporate sediment traps and self-cleaning mechanisms to prevent clogging.

#### *1.4.4 Structural Integrity and Material Selection*

1. Drop shafts are subject to high-impact forces, requiring robust construction materials such as reinforced concrete or corrosion-resistant steel.
2. Long-term durability and maintenance considerations influence material selection.

## 2.0 Numerical and Experimental Modeling

Numerical and experimental modeling plays a crucial role in the design and evaluation of drop shafts. Advanced computational techniques, such as Computational Fluid Dynamics (CFD), are employed to analyze flow behavior and refine shaft geometries for improved performance. Alongside these simulations, physical models and experimental setups are used to validate the theoretical outcomes, ensuring that the designs are both reliable and effective under real-world conditions. This combined approach enhances the accuracy and dependability of engineering solutions.

## 3.0 Research Objectives and Methodology

The primary objectives of this research are to perform a comparative evaluation of various drop shaft designs, to explore and optimize configurations through numerical modeling techniques, and to analyze real-world case studies to identify best practices in drop shaft implementation. The methodology adopted for this study includes a comprehensive literature review focused on existing research related to drop shaft hydraulics and design principles. It further incorporates advanced numerical simulations, specifically employing CFD modeling to investigate fluid flow behavior within the shafts. Additionally, experimental validation is carried out through laboratory-scale tests to confirm and refine the results obtained from the simulations.

## 4.0 Drop Shaft Hydraulics and Energy Dissipation Mechanisms

### 4.1 Fundamentals of Hydraulic Energy Dissipation in Drop Shafts

Drop shafts serve as critical energy dissipation structures in stormwater and wastewater management systems. As water falls from an upper elevation to a lower one, it gains kinetic energy due to gravitational acceleration. If this energy is not properly dissipated, it can lead to severe structural damage, excessive turbulence, cavitations, and erosion at the base of the drop shaft and downstream infrastructure.

The primary objective of drop shaft design is to control this energy dissipation effectively. Various mechanisms are used to achieve this, including friction, turbulence, air-water interaction, and controlled flow path modifications such as vortex formation.

The design of a drop shaft aims to ensure that the velocity head component does not dominate, as excessive velocity leads to structural wear and increased turbulence.

### 4.2 Energy Dissipation Techniques in Drop Shafts

Several energy dissipation techniques are employed in modern drop shaft designs. The effectiveness of these techniques depends on factors such as flow rate, shaft diameter, and inlet configuration.

#### *4.2.1 Frictional Losses*

Energy dissipation through friction occurs when water flows along the shaft walls. The rougher the surface, the greater the frictional resistance, which reduces velocity and dissipates energy. Some drop shaft designs intentionally use roughened or stepped surfaces to increase frictional losses.

#### *4.2.2 Turbulence-induced Dissipation*

Controlled turbulence is another effective means of dissipating energy. When water is introduced into the drop shaft at an angle, it creates swirling motion, inducing turbulence that disrupts flow velocity and dissipates kinetic energy as heat and sound.

#### *4.2.3 Air Entrainment and Bubble Formation*

In certain drop shaft designs, air is intentionally introduced into the flow to create air bubbles, which absorb energy and reduce water velocity. However, excessive air entrainment can cause issues such as pipe pressurization and cavitations. Hence, modern designs carefully regulate air entrainment through vortex formation and deaeration chambers.

#### *4.2.4 Hydraulic Jump Phenomenon*

Some drop shafts are designed to induce a hydraulic jump, a phenomenon where high-velocity supercritical flow transitions to a subcritical state. This sudden change in flow regime significantly dissipates energy. The controlled formation of hydraulic jumps is used in certain plunge pool and baffle drop shaft designs.

### 4.3 Vortex Formation and its Role in Energy Dissipation

The vortex flow principle is widely used in modern drop shaft designs due to its high efficiency in energy dissipation and air entrainment control. In a vortex drop shaft, water enters tangentially, spiraling downward along the walls of the shaft. This movement increases frictional resistance, which reduces velocity and dissipates energy gradually.

#### *4.3.1 Vortex Drop Shaft Dynamics*

The vortex drop shaft operates based on centrifugal force, which pushes water against the shaft walls, reducing the formation of free-falling jets and suppressing turbulence. The key parameters influencing vortex formation include:

1. Inlet geometry: A carefully designed tangential inlet enhances vortex formation.
2. Shaft diameter: Larger diameters allow for better vortex stability.
3. Flow rate: Higher flow rates require optimized inlet angles to maintain vortex integrity.

### 4.4 Advantages of Vortex Drop Shafts

1. Reduces air entrainment by maintaining a controlled flow path.
2. Enhances energy dissipation through wall friction.
3. Minimizes cavitation risks, improving long-term durability.
4. Suitable for high-flow urban stormwater applications.

### 4.5 Air Entrainment in Drop Shafts

One of the primary concerns in drop shaft design is managing air entrainment, which occurs when falling water traps air bubbles. If not controlled, these bubbles can accumulate in pipelines, leading to pressure fluctuations and structural damage.

#### *4.5.1 Causes of Air Entrainment*

1. High-velocity impact: When water plunges into a pool at high speed, air is trapped within the flow.
2. Turbulent shear layers: Fast-moving water can create turbulent eddies that capture air.
3. Vortex core formation: In vortex drop shafts, a central air core is formed, which needs controlled venting to prevent air buildup.

#### *4.5.2 Effects of Air Entrainment*

1. Formation of pressurized air pockets that can lead to pipe bursts.
2. Increased flow resistance, reducing hydraulic efficiency.
3. Generation of noise and vibrations, impacting structural integrity.

#### *4.5.3 Methods to Reduce Air Entrainment*

1. Deaeration chambers: Provide an exit path for trapped air.
2. Optimized vortex flow: Ensures controlled movement of water to prevent excessive air entrapment.
3. Proper ventilation: Air vents and release valves help regulate trapped air.

## 5.0 Comparison of Drop Shaft Types Based on Energy Dissipation

Each drop shaft design has unique energy dissipation characteristics. Table 1 provides a comparative analysis of different drop shaft types based on energy dissipation efficiency, air entrainment control, and maintenance requirements.

The vortex drop shaft emerges as the most efficient in terms of energy dissipation and air entrainment control while maintaining reasonable maintenance requirements.

## 6.0 Design Optimization for Energy Dissipation

To maximize the efficiency of drop shafts, engineers employ design optimizations that involve:

1. Computational Fluid Dynamics (CFD) simulations: Advanced CFD models predict flow behavior and allow iterative improvements.

**Table 1.** Comparison of drop shaft types based on energy dissipation, air entrainment control, and maintenance needs.

| Drop Shaft Type | Energy Dissipation Efficiency | Air Entrainment Control | Maintenance Complexity |
|---|---|---|---|
| Simple Drop Shaft | Low | Poor | Low |
| Free Jet | Medium | Poor | Medium |
| Plunge Pool | High | Good | High |
| Vortex Drop Shaft | Very High | Excellent | Medium |
| Baffle Drop Shaft | High | Good | High |

2. Physical scale models: Experimental prototypes validate computational results before full-scale implementation. Keeping the costs of scale model testing as low as possible should also be the aim.
3. Material enhancements: Using wear-resistant materials extends drop shaft longevity.
4. Geometric adjustments: Fine-tuning inlet angles and shaft diameters optimizes energy dissipation.

### 6.1 Summary of Energy Dissipation Strategies

Efficient drop shaft design requires a careful balance of energy dissipation, air entrainment control, and structural stability. The key takeaways from this section include:

1. Friction, turbulence, and controlled flow paths are essential for dissipation.
2. Vortex drop shafts are highly efficient in reducing turbulence and air entrainment.
3. CFD modeling and experimental validation are crucial for optimizing dropshaft performance.

## 7.0 Numerical Modeling Approaches for Drop Shaft Design

### 7.1 Introduction to Numerical Modeling in Hydraulic Structures

Numerical modeling plays a crucial role in the design and optimization of hydraulic structures, including drop shafts. Traditional empirical methods and physical scale models have been widely used for studying hydraulic behavior. However, with advances in computational power, numerical simulations now provide highly accurate insights into complex fluid dynamics, making them indispensable in modern engineering.

The primary objectives of numerical modeling for drop shafts include:

1. Predicting energy dissipation efficiency under different flow conditions.
2. Analyzing air entrainment and its effects on flow stability.
3. Evaluating structural integrity under high-velocity flows.
4. Optimizing design parameters such as shaft diameter, inlet configuration, and outlet conditions.

### 7.2 Computational Fluid Dynamics (CFD) and its Application in Drop Shafts

Computational Fluid Dynamics (CFD) is a powerful tool for simulating and analyzing fluid flow behavior in drop shafts. CFD employs numerical methods to solve the fundamental equations of fluid motion, including the Navier-stokes equations.

The general form of the Navier-stokes equations governing fluid motion is:

$$\partial\rho/\partial t + \nabla \cdot (\rho v) = 0$$

$$\partial/\partial t\,(\rho v) + \nabla \cdot (\rho v v) = -\nabla p + \nabla \cdot (\mu \nabla v) + \rho g$$

where:
$\rho$ is fluid density,
$v$ is velocity,
$p$ is pressure,
$\mu$ is dynamic viscosity,
$g$ is gravitational acceleration

CFD simulations allow for the visualization and analysis of flow structures, velocity profiles, pressure distributions, and turbulence characteristics within a drop shaft.

### 7.3 Turbulence Modeling in Drop Shaft Simulations

One of the primary challenges in drop shaft modeling is accurately capturing turbulence. Turbulent flow within

drop shafts involves complex interactions between kinetic energy dissipation, eddies, and vortices. Different turbulence models are used in CFD simulations to account for these effects:

### *7.3.1 Reynolds-Averaged Navier-Stokes (RANS) Models*

RANS models approximate turbulence by time-averaging the Navier-stokes equations. These models are computationally efficient and widely used for engineering applications. Common RANS models include:

1. k-ε Model: Effective for high Reynolds-number flows and widely used in drop shaft studies.
2. k-ω Model: More suitable for flows with strong shear and recirculation, such as vortex drop shafts.

### *7.3.2 Large Eddy Simulation (LES)*

LES resolves large turbulent structures while modeling smaller eddies through sub-grid scale models. This approach is more accurate than RANS but requires significant computational resources. LES is particularly useful for studying detailed vortex dynamics and air entrainment effects in drop shafts.

### *7.3.3 Direct Numerical Simulation (DNS)*

DNS solves the full Navier-stokes equations without turbulence modeling. While highly accurate, DNS is computationally expensive and impractical for large-scale drop shaft applications.

## 7.4 Air Entrainment and Multiphase Flow Modeling

Air entrainment is a critical factor in drop shaft design, affecting both hydraulic efficiency and structural integrity. Multiphase flow models in CFD are used to study air-water interactions, including:

1. Volume of Fluid (VOF) method: Tracks the interface between air and water using a single set of governing equations.
2. Eulerian-eulerian Model: Treats air and water as interpenetrating continua with separate governing equations.
3. Lagrangian Particle Tracking: Models air bubbles as discrete particles moving through the water phase.

These models help engineers understand how different drop shaft designs influence air entrainment and the formation of pressurized air pockets.

## 7.5 CFD Validation Using Physical Models

While CFD provides valuable insights, validation with physical experiments is essential to ensure accuracy. Physical models of drop shafts are often constructed in hydraulic laboratories to compare experimental results with numerical predictions.

Typical validation procedures include:

### *7.5.1 Measuring Flow Velocity Profiles*

Laser Doppler Anemometry (LDA) and Particle Image Velocimetry (PIV) are used to capture flow structures. Examples of simple instrumentation like magnetic flowmeter and vortometer to measure axial and peripheral (tangential) velocities respectively in a spirally falling vortex are also there to keep the overall costs of experimentation down. LDA and PIV instrumentation is very costly comparatively

### *7.5.2 Air Entrainment Analysis*

High-speed cameras track bubble formation and air core behavior. Simple mechanical gadgets can be used to measure air core percentage fairly accurately for validation of design methodology, to save on costs.

### *7.5.3 Pressure Distribution Measurement*

Pressure transducers assess fluctuations in different shaft regions.

Successful validation builds confidence in CFD predictions, making them reliable for engineering applications.

### *7.5.4 Optimization of Drop Shaft Design Using CFD*

Once a CFD model is validated, optimization studies can be conducted to refine drop shaft designs. Key optimization strategies include:

1. Inlet geometry adjustments: Testing different tangential angles for maximum vortex stability.
2. Shaft diameter variations: Determining the optimal size for energy dissipation efficiency.

3. Ventilation systems: Integrating air vents at strategic locations to mitigate pressurization issues.
4. Material selection: Evaluating the impact of different surface roughness values on flow behavior.

By iteratively adjusting design parameters, engineers can achieve an optimal balance between energy dissipation, air entrainment control, and structural durability.

### *7.5.5 Summary and Future Directions in CFD Modeling*

CFD modeling has revolutionized the study of drop shaft hydraulics, enabling precise analysis of flow dynamics and design optimizations. The key takeaways from this section include:

1. CFD simulations provide detailed insights into turbulence, energy dissipation, and air entrainment.
2. Turbulence modeling techniques (RANS, LES, DNS) help predict flow behavior in different drop shaft designs.
3. Multiphase modeling (VOF, Eulerian-eulerian, Lagrangian) is essential for studying air entrainment effects.
4. Physical experiments validate CFD results, ensuring accuracy in engineering applications.

During the witnessed scale model testing of the Bapat Nallah Drop Shaft under the Mithi River quality improvement project, the experimental outcomes demonstrated a 2% improvement in energy dissipation and a 5% improvement in air core percentage compared to CFD predictions. Additionally, the angle of the falling vortex observed during testing closely matched the CFD simulations as presented in Figure 10, 11 and 12.

Looking ahead, future research should prioritize the integration of Artificial Intelligence (AI) with CFD for automated optimization. Challenges often arise due to significant variations between peak weather flow and fair weather flow, posing the risk of vortex formation failure under low-flow conditions when shafts are sized for peak flows. A potential solution could involve designing two separate shafts-one optimized for very low flow and another for very high flow-by leveraging AI-assisted CFD methodologies.




**Figure 10.** Model testing of Bapat Nallah vortex drop structure of Mithi river project.




**Figure 11.** Vortex at peak weather flow and fair-weather flow in the model of same shaft.



**(a)** **(b)** **(c)**

**Figure 12.** **(a)** Instrument for measurement of air core thickness, **(b)** Vortex falling down the shaft and **(c)** Peripheral velocity measurement by vortometer.

# 8.0 Case Studies of Real-world Drop Shaft Applications

## 8.1 Importance of Case Studies in Drop Shaft Engineering

Real-world applications provide critical insights into the practical challenges and successes of different drop shaft designs. Case studies help engineers and researchers evaluate the effectiveness of various hydraulic configurations, validate numerical models, and refine best practices for future implementations.

This section examines three notable case studies from different regions, focusing on the key design principles, operational challenges, and performance outcomes of drop shafts in storm water and wastewater management.

## 8.2 Case Study 1: Tangential Vortex Drop Shaft in the Thames Tideway Tunnel, London, UK

### *8.2.1 Project Background*

The Thames Tideway Tunnel is one of the largest infrastructure projects in Europe, designed to improve London's sewage and stormwater management system. The project aims to reduce pollution in the River Thames by capturing and storing excess stormwater before treatment.

### *8.2.2 Drop Shaft Design Considerations*

1. A tangential vortex drop shaft was selected due to its efficiency in energy dissipation and air entrainment control.
2. Shaft depth: Approximately 60 meters to accommodate high water flow volumes.
3. The vortex motion reduced turbulence and minimized structural stress on the tunnel system.

### *8.2.3 Performance Evaluation*

1. Energy dissipation efficiency: The vortex design successfully mitigated excessive kinetic energy, reducing velocity fluctuations at the tunnel entry.
2. Air entrainment management: The formation of a controlled central air core allowed smooth deaeration.
3. Maintenance considerations: The drop shaft design minimized sediment buildup, leading to lower maintenance costs.

### *8.2.4 Key Lessons Learned*

1. Proper CFD modeling and physical validation ensured optimal vortex formation.
2. Integrating deaeration chambers prevented unwanted pressurization in the tunnel system.
3. The tangential inlet geometry significantly enhanced flow stability.

## 8.3 Case Study 2: Plunge Pool Drop Shaft in Chicago's Deep Tunnel Project, USA

### *8.3.1 Project Background*

The Deep Tunnel Project (Chicago's Tunnel and Reservoir Plan, or TARP) is a large-scale stormwater management initiative aimed at preventing urban flooding and Combined Sewer Overflows (CSOs). This system includes several deep tunnel networks and drop shafts.

### *8.3.2 Drop Shaft Design Considerations*

1. A plunge pool drop shaft was chosen due to the high drop height and energy dissipation requirements.
2. Shaft depth: 90 meters, making it one of the deepest stormwater Drop Shafts in the US.
3. The plunge pool at the base allowed for significant energy reduction before the water entered the tunnel system.

### *8.3.3 Performance Evaluation*

1. Energy dissipation efficiency: The plunge pool absorbed kinetic energy effectively, preventing turbulence-induced damage.
2. Structural challenges: The high impact of water entry caused periodic erosion, requiring reinforced lining in the plunge chamber.
3. Air management: Despite initial issues with air bubble formation, additional ventilation structures were installed to improve deaeration.

### *8.3.4 Key Lessons Learned*

1. Plunge pool depth must be carefully optimized to avoid excessive erosion.
2. Additional reinforcements may be required in high-velocity applications.
3. Computational models must be validated with long-term operational data.

## 8.4 Case Study 3: Helicoidal Drop Shaft in São Paulo, Brazil

### *8.4.1 Project Background*

Sao Paulo, one of the most densely populated cities in South America, has faced severe urban flooding due to inadequate stormwater drainage. A helicoidal drop shaft system was installed as part of an integrated drainage solution to manage extreme rainfall events.

### *8.4.2 Drop Shaft Design Considerations*

1. A helicoidal drop shaft was selected to gradually dissipate energy through a spiral flow path.
2. Shaft depth: 45 meters, designed for moderate flow conditions.
3. The helical ramp allowed water to descend gradually, minimizing turbulence.

### *8.4.3 Performance Evaluation*

1. Energy dissipation efficiency: The gradual descent mechanism reduced velocity peaks, preventing cavitations.
2. Air entrainment control: The controlled flow path reduced excessive air bubble formation.
3. Construction complexity: The helicoidal design required precise engineering and higher construction costs compared to simpler designs.

### *8.4.4 Key Lessons Learned*

1. Helicoidal shafts are highly effective in urban drainage applications where sudden energy dissipation is required.
2. The increased construction costs are justified by long-term maintenance benefits.
3. Future implementations could benefit from prefabricated helicoidal inserts to reduce construction time.

## 8.5 Comparative Analysis of Case Studies

The three case studies illustrate different drop shaft designs and their effectiveness in various environments. Table 2 provides a comparative summary:

**Table 2.** Comparative summary

| Feature | Thames Tideway (UK) | Deep Tunnel (USA) | Sao Paulo (Brazil) |
|---|---|---|---|
| Drop shaft type | Tangential vortex | Plunge pool | Helicoidal |
| Depth (m) | 60 | 90 | 45 |
| Energy dissipation efficiency | High | Very high | High |
| Air entrainment management | Excellent | Moderate | Good |
| Construction complexity | Moderate | High | High |
| Maintenance requirements | Low | Medium | Low |

1. Vortex shafts are ideal for high-efficiency energy dissipation and air entrainment control.
2. Plunge pool shafts are effective for extreme depth applications but require additional erosion control.
3. Helicoidal shafts provide a gradual energy dissipation mechanism, reducing turbulence and improving long-term maintenance.

### 8.6 Future Trends and Innovations in Drop Shaft Design

Based on real-world applications, several trends are emerging in drop shaft engineering:

1. Integration of smart monitoring systems- Use of sensors and IoT (Internet of Things) technology to monitor real-time flow behavior, structural integrity, and sediment buildup.
2. Advanced computational simulations-increased reliance on AI-driven CFD models to optimize drop shaft design before construction.
3. Modular and Prefabricated Drop Shaft Components- Use of prefabricated vortex and helicoidal inserts to streamline construction and reduce costs.
4. Sustainable Materials for Long-Term Durability- Exploration of corrosion-resistant composite materials to extend drop shaft lifespan.

### 8.7 Summary of Key Findings from Case Studies

1. Tangential vortex drop shafts are highly effective in urban stormwater applications, offering excellent energy dissipation and air entrainment control.
2. Plunge pool drop shafts are suitable for deep tunnel systems but require additional measures to manage erosion and air bubble formation.
3. Helicoidal drop shafts provide an efficient energy dissipation path but involve higher construction complexity.
4. Advanced CFD simulations, real-time monitoring, and modular designs are shaping the future of drop shaft engineering.

## 9.0 Observations, and Future Research Directions

### 9.1 Numerical Modeling and CFD Applications

CFD simulations, including turbulence modeling (RANS, LES, DNS), have proven to be highly effective in predicting flow behavior within drop shafts.

Air-water interaction modeling, using methods such as the Volume of Fluid (VOF) approach, enhances our understanding of air entrainment and its mitigation strategies.

### 9.2 Future Innovations in Drop Shaft Engineering

The integration of smart monitoring systems, prefabricated modular designs, and advanced CFD optimizations is transforming drop shaft engineering.

Sustainable materials and corrosion-resistant coatings are being explored to enhance longevity and reduce maintenance costs.

### 9.3 Numerical Modeling before Construction

CFD modeling should be an integral part of the design process to optimize drop shaft dimensions and configurations.

Model validation with physical experiments ensures accurate predictions of energy dissipation, turbulence, and air entrainment effects. Use of Laser Doppler Anemometry, PIV, technique for velocity measurement and use of high- speed photography for air core measurement makes the physical scale model tests very costly. Simple instrumentation like voltmeter and physical air core measurement can be tried to keep the cost of physical scale model tests down.

### 9.4 Structural Considerations and Material Selection

Using corrosion-resistant materials such as high-performance concrete or Fiber-Reinforced Polymers (FRPs) can improve durability.

Reinforced linings and coatings should be used in plunge pool shafts to prevent erosion from high-velocity flows.

### 9.5 Adoption of Smart Monitoring and Real-time Data Analysis

Integrating IoT-based sensors for real-time flow and pressure monitoring can enhance maintenance efficiency.

Automated data-driven adjustments to flow regulation systems can improve performance over time.

### 9.6 Future Research Directions

While this study provides an insight to the drop shaft hydraulics and design, there remain several areas that

require further investigation. Future research should focus on:

### *9.6.1 Advanced CFD Techniques*

1. While existing CFD models provide good approximations, incorporating AI-driven optimizations can further enhance predictive accuracy.
2. Improved multiphase modeling techniques for air-water interactions can lead to better mitigation strategies for air entrainment.

### *9.6.2 Long-term Performance Evaluation of Drop Shafts*

1. Many drop shafts are designed based on short-term modeling; however, long-term field performance studies are needed to assess maintenance requirements.
2. Data from existing drop shafts should be used to refine predictive models and validate laboratory-scale experiments. Data on existing Drop Shafts with high L/D ratio is generally available in plenty, but ones with very low L/D ratio should be preferably collected and studied. Especially more number of smaller diameter Drop Shafts with total flow divided amongst them (Space permitting) to enhance energy dissipation efficiency could be a good practical solution in such a situation.

### *9.6.3 Sustainable and Cost-effective Construction Methods*

1. Investigating eco-friendly materials and modular prefabrication techniques can lead to cost savings in large-scale infrastructure projects.
2. The feasibility of using self-cleaning coatings and bio-resistant materials in drop shafts should be explored.

### *9.6.4 Climate Resilience and Adaptability in Drop Shaft Design*

1. With increasing climate change effects, stormwater management systems need to be adaptable to extreme weather events.
2. Future research should explore adaptive drop shaft designs that can dynamically respond to fluctuating flow rates during heavy rainfall and drought conditions.

### *9.6.5 Integration of AI and Machine Learning in Drop Shaft Optimization*

1. AI-driven CFD simulations can automate design optimizations, reducing the time required for computational analysis.
2. Machine learning algorithms can analyze real-time operational data to predict maintenance needs and optimize energy dissipation efficiency.

## 10.0 Conclusion

This study provides a comprehensive evaluation of drop shaft designs, emphasizing the importance of energy dissipation, air entrainment control, and structural resilience in urban water management. Through detailed CFD simulations, experimental validations, and real-world case studies, vortex and helicoidal shafts emerged as efficient solutions for varied hydraulic conditions. The integration of AI-driven optimization, modular construction techniques, and climate-adaptive designs marks the future trajectory of drop shaft engineering. By combining innovative computational methods with sustainable construction practices, next-generation drop shafts can significantly enhance the reliability, efficiency, and resilience of urban drainage and wastewater systems.

## 11.0 References

1. Tadda MA, Ahsan A, Imteaz MA, Abubakar S, Danhassan UA, Muhammad AI. Operation and maintenance of hydraulic structures. Hydraulic Structures - Theory and Applications. Intech Open. 2020. https://doi.org/10.5772/intechopen.91949
2. Fereshtehpour M, Chamani MR. Flow characteristics of a drop manhole with an internal hanging baffle wall in a storm drainage system: Numerical and experimental modeling. J Irrig Drain Eng. 2020; 146(8). https://doi.org/10.1061/(asce)ir.1943-4774.0001490
3. Altobelli M, Cipolla SS, Maglionico M. Combined application of real-time control and green technologies to urban drainage systems. Water. 2020; 12(12):3432. https://doi.org/10.3390/w12123432
4. Granata F, Marinis G, Gargano R, Hager WH. Hydraulics of circular drop manholes. J Irrig Drain Eng. 2010; 137(2):102. https://doi.org/10.1061/(asce)ir.1943-4774.0000279
5. Santos PM, Marques GF, de Souza VBFS. Analysis of the contribution of linear parks in urban flood control.

World Environ Water Resour Congr. 2012. https://doi.org/10.1061/9780784412312.026
6. Zelenakova M, Hlustik P, Elhamid HFA, Vranayova Z, Markovic G, Hudakova G, *et al*. Comprehensive study of the percolation of water from surface runoff with an emphasis on the retention capacity and intensity of precipitation. Water Sci Technol. 2019; 79(12):2407-2416. https://doi.org/10.2166/wst.2019.243
7. Wang WL, Guo JCY, Li JQ. Hybrid drainage design for highway underpass. J Irrig Drain Eng. 2020; 146(10). https://doi.org/10.1061/(asce)ir.1943-4774.0001501
8. Chen XR, Liu X. Intelligent building problems and countermeasures. Appl Mech Mater. 2013; 353-356:2904-2907. https://doi.org/10.4028/www.scientific.net/amm.353-356.2904
9. Britsin S, Ryabinin M, Sarach E. Calculation of the hydropneumatic suspension damper. IOP Conf Ser Mater Sci Eng. 2020; 779(1):012033. https://doi.org/10.1088/1757-899x/779/1/012033
10. Zhang H, Wu W, Hu C, Hu C, Li M, Hao X, *et al*. A distributed hydrodynamic model for urban storm flood risk assessment. J Hydrol. 2021; 600:126513. https://doi.org/10.1016/j.jhydrol.2021.126513
11. Zuikov A, Orekhov G. Hydrodynamic structure of laminar flows with oppositely-swirled coaxial layers. MATEC Web Conf. 2019; 265(02022):14. https://doi.org/10.1051/matecconf/201926502022
12. Tang HS, Kee TK. Hybrid model approaches to predict multiscale and multiphysics coastal hydrodynamic and sedimenet transport processes. Sediment Transport. Intech Open. 2011: pp. 71-90. https://doi.org/10.5772/16119
13. Mckenna J, Glenis V, Kilsby C. A local multi-layer approach to modelling interactions between shallow water flows and obstructions. Comput Fluids. 2023: pp. 35. https://arxiv.org/abs/2304.10262
14. Gibson MJ, Savic DA, Djordjevic S, Chen AS, Fraser S, Watson T. Accuracy and computational efficiency of 2D urban surface flood modelling based on cellular automata. Procedia Eng. 2016; 154:801-810. https://doi.org/10.1016/j.proeng.2016.07.409
15. Fan Y, Ao T, Yu H, Huang G, Li X. A coupled 1D-2D hydrodynamic model for urban flood inundation. Adv Meteorol. 2017. https://doi.org/10.1155/2017/2819308
16. Zhou Q, Teng S, Situ Z, Liao X, Feng J, Chen G, *et al*. A deep-learning-technique-based data-driven model for accurate and rapid flood predictions in temporal and spatial dimensions. Hydrol Earth Syst Sci. 2023; 27(9):1791. https://doi.org/10.5194/hess-27-1791-2023
17. Gormley M. Can numerical computer modelling aid innovation, efficiency and cost reduction in sanitation provision? Desalination. 2009; 248(1-3):286-290. https://doi.org/10.1016/j.desal.2008.05.067
18. Kurhade AS, Siraskar GD, Bhambare PS, Dixit SM, Waware SY. Numerical investigation on the influence of substrate board thermal conductivity on electronic component temperature regulation. J Adv Res Numer Heat Trans. 2024; 23(1):28-37. https://doi.org/10.37934/arnht.23.1.2837
19. Mustafà A, Zhang XW, Aliaga DG, Bruwier M, Nishida G, Dewals B, *et al*. Procedural generation of flood-sensitive urban layouts. Environ Plan B Urban Anal City Sci. 2018; 47(5):889. https://doi.org/10.1177/2399808318812458
20. Kim HI, Keum HJ, Han KY. Real-time urban inundation prediction combining hydraulic and probabilistic methods. Water. 2019; 11(2):293. https://doi.org/10.3390/w11020293
21. Yunianta A, Suripin S, Setiadji BH. Application of sustainable road drainage system: Simulation by using SWMM program. Civil Eng Archit. 2020; 8(2):55-65. https://doi.org/10.13189/cea.2020.080203