97 Acid plating with zinc—

T. Jelinek and K. J. Munch, Metall. 24-6 (1970) 640; Zinc Abs. No. 6699 (1970). Acid zinc plating electrolytes, their characteristics, and the properties of electrodeposited zinc coatings.

98 Some mechanical properties of zinc electrodeposits—

D. John, Metalloberflache, 24-7 (1970) 229. Electrodeposition and some mechanical properties of zinc from various cyanide, sulphate and chloride baths.

99 Kinetics of high-temperature oxidation of dispersion-strengthened nickel-niobia alloys—

T. H. Rao and K. I. Vasu, Proc. Symp. Materials Science Research, Bangalore 1970, Vol. II, p. 134. Nickel-niobia alloys are inferior to nickel in oxidation resistance. Three stages of oxidation in these alloys. 4 tables, 2 figs, 46 refs.

100 Stress corrosion of some Al-Zn and Al-Mg alloys—

R. Chandrashekar and K. I. Vasu, Proc. Symp. Materials Science Research, Bangalore 1970, Vol. II. p. 150. The potential-time curves during SCC explained by the electrochemical theory: Effect of ageing and specimen size and shape on SCC. 2 tables, 8 figs, 16 refs.

101 Developments in oxidation and Corrosion resistant materials—

N. S. D. Elayathu and J. Balachandra, Proc. Symp. Materials Science Research, Bangalore 1970, Vol. II. p. 96. Review of oxidation and corrosion phenomenon and the materials which can withstand these. 3 tables, 3 figs, 26 refs.

—K. I V.

(B) CORROSION

1 Reaction of Co-Ni-V alloys with O_2 at 1351 to 1429°K—

R. M. Doerr and J. W. Jensen, U.S. Bur. Mines, RI 7371 (1970). The effect of vanadium additions on the oxidation of Co-Ni alloys around 1000°C. The rate was parabolic in most cases with large early deviations. Addition of vanadium increases the oxidation, probably due to the valency effect and the formation of law-melting phases.

2 Cyclic oxidation of nickel - base alloys and heat - resisting steels–

M. J. Fleetwood and J. E. Whittle, Brit. Corr. J. 5-3 (1970) 131. Weight changes of Ni-Cr and Fe-Ni-Cr alloys oxidized in air for up to 1000 hrs under cyclic conditions (15 min. in furnace around 1100°C followed by 5 min. cooling below 300°C) are related to the microstructure of alloys after exposure. Initial oxidation to form a protective scale occurred faster than predicted on the basis of isothermal oxidation data; subsequent spalling of the scale was reduced by high contents of Ni and Cr, and by minor additions of Si, Ce and Al.

3 Oxidation of commercial high-temperature alloys–

S. K. Rhee and A. R. Spencer, Met. Trans. 1(1970) 2021. Selective oxidation of Cr. in wire specimens of four alloys. Parabolic kinetics.

Evaluation of oxidation - resistant-alloy cladding–

M. A. Gedwill, NASA Tech. Note D-5483 (1969) 34 pp; Cobalt, Abs. No. 49-61. An investigation to explore the feasibility of using oxidation resistant cladding alloys to protect superalloys during cyclic furnace oxidation

5 Controlled viscosity coatings for superalloys–

R. B. Grekila, J. W. Chapman and D. M. Mattox, Nasa CR No. 72520 (1969) 100 pp.; Cobalt, Abs. No. 49-62. The feasibility of glass-based protective coatings for the superalloys, TD-Ni, etc.

6 Oxidation - resistance of aluminide-coated superalloys–

E. P. Whelan and R. V. Dainty, AD 700882 (1969); Cobalt, Abs. No 49-63. Six oxidation-sulphidation resistant aluminide coatings were applied on super-alloys, and their oxidation behaviour under cyclic tests determined.

7 Liquid corrosion of hard alloys a high temperatures

V. A. Zhilin and V. M. Druzhinin Porosh. Metall (Russ) No. 2 (1970) 95; Cobalt, Abs. No. 49-98. The corrosion of WC-Co cutting tools by the cooling liquids was studied. The degree of corrosion reached a maximum at 600 to 650°C, falling rapidly and reaching a minimum at 1000°C when the cooling liquids vaporize and the gaseous interlayer protects the surface from attack.

8 Effect of alloying and heat treatment on the strength and cavitation resistance of alloys with age-hardenable martensite–

L. S. Malinow et al, Energomashinostroy. (Russ) No. (1967) 29, Cobalt, Abs. No. 49-113. In an attempt to find a cavitation-resistant material for hydraulic turbines, several maraging compositions were studied. After annealing and quenching. all steels contain 80-90% martensite except a Ni-Co-Mo-Ti-Al Steel which contained 45%. In spite of its lower martensite content, this steel has the highest hardness and cavitation resistance, probably associated with an improvement of the resistance of both martensite and austenite to micro-impacts.

9 An accelerated stress corrosion test–

A. H. Freedman, J Mat. 5 (1970) 431. Single-edge-notched and fatigue cracked specimens were tension loaded in NaCl solution and the threshold

stress-intensity factor for stress corrosion determined. The aggressive corrodant, the presence of a crack, and the plane strain loading conditions reduce the test time.

10 Effect of composition and strength on the susceptibility of alloy steels to cadmium plating (hydrogen) embrittlement—

P. F. Langstone, AD 703590 (1968) 33 pp ; Corrosion, Abs. No. 49-116, Small-grain-size maraging steels are resistant to Cd-plating embrittlement probably due to entrapment of H_2 at precipitates and to the locking of dislocations in the structure.

11 Hydrogen embrittlement of maraging steels—

C. B. Sonnino and H. C. Tourkakis-Cobalt, Abs. No. 49-117. The effects of cathodic charging on samples quenched from 815°C and aged for 3h at 480°C. The tensile strength of notched specimens was reduced after charging with hydrogen. Endurance tests on notched specimens were more sensitive to hydrogen embrittlement.

12 Development of maraging steels with improved properties :

J. L. Castagne, 'Steel-Strengthening machanisms', Climax Molybdenum Co., 1970, pp 89-95 ; Cobalt, Abs. No. 49-118. By adjusting the composition to reduce the number of electron vacancies (reducing Mo and substituting Co for part of Fe), an alloy was obtained which does not suffer from embrittlement and exhibits excellent corrosion resistance in HNO_3.

13 Application of maraging steels in chemical industry—

H. Spahn and L. Kopp, Chemie-Ing. Tech. 41 (1969) 1243 ; Cobalt, Abs. No. 49-119. Corrosion resistance in KCl, $Na_2SO_4 + H_2SO_4$, and acetic acid of 18Ni-Co-Mo and Ni-Cr-Co-Mo steels. These steels are suitable for pressure vessels in industry

14 Corrosion resistance of cobalt-bearing aluminium bronzes–

M. Leoni, Inst. Sperimment. Metall Leg. Reg. No. 68/17 661 (1968) 13 pp Cobalt, Abs. No. 49-140 ; M. Leonic and G. Fortina, Rep. No. 69/19920 (1969) 16 pp ; Cobalt, Abs. 49-141. Checking the resistance of the alloys to dealuminization, a type of corrosion frequently encountered in aluminium bronzes used for sea-water desalting plants.

15 Development of hot-corrosion resistant cobalt-base alloys for marine applications--

N. T. Wagenheim, Cobalt, 48 (1970) 129. The MELCO-14 alloys with 0.4C, 0.3Mn, 28Cr, 10Ni, 7.5W, 3Ta, 0.015B, 0.15Y, ;0.5Hf and bal. Co provided the best compromise between hot-corrosion resistance and stess rupture strength.

16 Role of rare earth additions in hot corrosion—

A. U. Seybolt, Cobalt, Abs. No. 48-66. The mechanism by which small rare-earth additions to nickel-base superalloys considerably reduce the degree of hot-corrosion of these alloys, apparently by reducing the amount of various sulphides formed.

17. Stress corrosion cracking behaviour of an 18% maraging steel,

A.J. Stavros, Cobalt, Abs. No. 48-120. SCC of the steel using precracked cantilever beam specimens – intergranular cracks except in specimens austenitized at 815°C exhibited crack branching. Fractography revealed no difference due to change in solution, pH, or applied potential.

18 Effect of environment on stress-induced failure of steels—

H. P. Lockie, Cobalt, Abs. No. 48-121. SCC of 12 and 18% Ni maraging steels. Short times to failure may be induced by the application of active potentials giving failure by hydrogen embrittlement. High conc. of OH^- ions inhibit SSC while low conc. stimulate the process.

19, Effect of trace impurities on SCC of maraging steels—

R.P.M. Procter and H.W, Paxton' Cobalt, Abs. No. 48-122. Deliberate impurity addition of S, P, C. Cr, Si and Mn to 18% Ni maraging steels. Ultra-pure steels do not have improved SC resistance and C more than 0.03% result in marginally improved SC resistance while Cr result in poor SC properties.

20. Stress corrosion resistance and fatiuge of a stainless steel.—

D- Webster, AD 695 794 (1969) 9 pp; Cobalt, Abs. No. 48-122. The plain-strain stress corrosion is markedly affected by the tempering temp. and the degree of strain ageing.

21. Corrosion of partial-denture alloys–

L. F. Allard and k. Asgar, Cobalt. Abs. No. 48-136. The influence of oral conditions on the corrosion of the dental alloys.

22. Corrosion of surgical implant materials.

R.W. Revie and N.D, Greene, Corr. Sci. 9 (1969) 755. The effect of different sterilization and surface treatment on the subsequent corrosion rates of four alloys. Prepassivation of types 304 and 316 stainless steels and vitallium in oxygenated isotonic NaCl is preferable to any form of HNO_3 passivation treatment.

23. Corrosion in coal mines—

W. S. Evans and S. Wiktorek, Austr. Cor. Eng. 14-9 (1970)7. The causes of corrosion of main equipment and the methods to minimise its effects, as a result of experience and service trials. 1 table, 9 figs. 18 refs.

24 Corrosion-erosion problems at a coal cleaning plant—

W. Hayter, Austr. Corr. Eng. 14-9 (1970)17. Corrosion-erosion problems at each stage and the steps to overcome these problems. 2 tables, 6 figs.

25. Zinc coated steel prevents car body Corrosion—

F.C. Porter and G.K. Walden, Corr. Prevention Control, 17 5 (1970) 10. Galvanized steel is used for parts of vehicles exposed to road wash corrosion problems.

26 Reliability and Corrosion—

R.D, Barer, Anti – Corrosion,17-10 (1970) 10. Metallurgical aspects of corrosion-case histories from different environments – aluminium, and its alloys, steels, brasses. 30 figs, 7 refs.

27 Development of stress-corrosion resistant aluminium alloy forgings—

J.V. Luhan and T J. Summerson, Metals Eng Quart. 10-4 (1970) 35 Overageing improves the stress-corrosion resistance of Al-Zn-Mg alloys. The alloys 7049 T73 offers a good combination of alloying elements, fabrication processes and heat treatments, making possible high strength while retaining stress-corrosion immunity. 8 tables, 9 figs, 3 refs.

28 New horizons in characterizing corrosion processes—

R. C. Carlston, Metals Eng. Quart. 10-4 (1970) 30. The numerous techniques which promise to give a more scientific basis for corrosion control. 1 fig, 62 refs.

29 New reactive primer for provisional protection against corrosion—

J. Ivanfi, Korr. figyelo, 10-5 (1970) 134. New reactive primer, surface pretreatment, coating and drying, and the resistance of the coat to heat, cold, gasoline, water and salt smog. Weldability of the coat, finishing and storing aspects. 8 figs, 15 refs.

30 Corrosion of stainless steel in sodium sulphate solutions containing hydrogen sulphide—

G. Szoboszlay, Korr. figyelo, 10-5 (1970) 145. A combination of $CuSO_4$ and alcoholic or carbonyl compounds inhibit the corrosion of CrNiMo stainless steel in H_2SO_4-Na_2SO_4-H_2S solutions at 85 C. 14 refs.

31 Problems of protecting the inner surface of aluminium vessels storing food and drinks—

S. Egerhazi and Mrs. E. T. Szolga, Korr, figyelo, 10-5 (1970) 150. The effect of aluminium on foodstuffs and drinks. Techniques of aluminium surface treatment, electro-chemical and lacquer coatings. 4 tables.

32 The properties of phosphate coating on aluminium castings–

Mrs. S. K. Weinmeier, Korr. figyelo, 10-5 (1970) 155. Phosphatizing-quality and rate of formation. X-ray test shows hopeit, $Zn_3(PO_4)_2 . 4H_2O$, on the surface. Porosity, adhesion surface hardness, heat and corrosion resistance etc.

33. History of cathodic protection –

L. Krivian, Korr. figyelo, 10-4 (1970) 101. Formulations of cathodic protection and the field of utilization of the method. Some data about the spreading use of cathodic protection. 3 tables.

34. Technical conditions of electrophoretic painting and their control -

J. Gehring, Korr. figyelo, 10-4 (1970) 104. Basic principles and processes of electrophoretic painting, the electrochemical equivalent by deposition, throwing powder, penetrating power etc. 3 tables, 4 figs, 4 refs.

35. Influence of Fe(II)-content and temperature on the solubility of scale in pickling baths :

M. Balla and E. Berecz, Korr, figyelo, 10-4 (1970) 109. The scale solubility in $FeCl_2$-HCl-H_2O and $FeCl_2$-H_2So_4-H_2O systems. 1 table, 8 figs, 4 refs.

36. Some corrosion problems in plants producing household chemicals :

J. Pataki, Korr. figyelo, 10-4 (1970) 121. The advantageous results of polypropylene and polyester materials in a plant producing household chemicals.

37. Corrosion resistance of cadmium coatings :

T. Biestek, Galvanotech. 61-10 (1970) 806. Tests of corrosion rates of cadmium deposits in industrial, municipal, sea and open country atmospheres. 4 tables, 4 figs, 25 refs.

38. Alleged stress corrosion cracking of pure copper :

H. H. Uhlig and D. T. Duqette, Corr. Sci. 9 (1969) 557. The occurrence of SCC of 99.999% Cu foil in oxygenated ammonia solution is improbable and the failure reported can be explained by intergranular corrosion.

39. Mechanism of SCC in Cu-Al alloys :

A. W. Blackwood and N. S. Stoloff, Trans. ASM, 62 (1969) 677. The susceptibility of SCC of Cu-Al alloys depends on alloy content, Cu-ion content, pH and stress level.

40. Effects of corrosion inhibitor on SCC of aluminium brass :

S Sato and T. Nosetani, Copper Abs. No. 162 (1970). Addition of inhibitor is useful for preventing SCC of aluminium brass in fresh water.

41. Dichromate as inhibitor for the corrosion of Cu in HCl :

I A Ammar and S. Riad, Corr. Sci. 9 (1969) 423. A critical conc. of dichromate is an effective inhibitor for corrosion of copper in HCl at 30°C.

42. Benzotriazole as an effective corrosion inhibitor for Cu alloys :

Copper Abs. No. 261 (1970). Benzotriazole forms a strongly bonded chemisorbed barrier film which protects Cu and its alloys in aq. media, various atmospheres, lubricants and hydraulic fluids.

43. Inhibition of corrosion of 67/37 brass in nitric acid :

M. N. Desai et al, Brit. Corr. J,, 4 (1969) 309. O-Anisidine, O-phenetidine and O-toluidine as corrosion inhibitors for brass.

44. Corrosion inhibition aad corrosion promotion of zinc by phosphate ions :

S. A. Awad and K. M. Kamel, J. Electroanal. Chem. Interface. Electrochem. 24-1 (1970) 217. Above pH 4.6, a positive shift of potential occurs at a definite posphate conc., due to a protective interface of complex phosphate ions adsorbed on a persisting zinc phosphate layer.

45. Use of envirormental data in atmospheric corrossion studies :

J. F. Stanners, Brit. Corrosion J. 5-3 (1970) 117. Correlation of meteorological and pollution data with the corrosion kinetics of bare and coated metals – empirical and theoretical standpoints.

46. Atmospheric corrosion behaviour of galvanized sheets :

H. Wiegand and K. H. Kloos, Stahl Eisen, 90–11 (1970) 587. The influence of the continuous galvanizing process on the cold forming and spot welding characteristics of steel sheeting. Changes in the surface of zinc coating resulting from welding and forming operations.

—K. I. V.