Ghandhi and C. P. Shah, Anti-Corrosion Methods Materials,18-4(1971)8. Review of the corrosion inhibitors for aluminium and aluminium alloys in water, sea water and salt solutions and and alkaline media. 99 refs.

26. On the future in electrochemical energy conversion and storage-

J. O'M Bockris, Trans. SAEST, 6-2 (1971) 37. General review. Inevitability of large scale introduction of electrochemical power sources. Fuel cells and batteries. Energy Storage. Electrochemical energy conversion. Education, training and attitude. The electrochemical world. 2 tables, 15 figs, 22 refs.

27. Porous electrodes and their theoretical models-

Karel Micka, Trans. SAEST, 6-2(1971) 50. A general review. Theoretical concepts; porous gas electrodes. 57 refs.

28. Relation between macro- and micro-kinetic characteristics of liquid porous electrode operation-

I.G. Gurevich, Trans. SAEST, 6-2(1971)55. Attempts to systematise the relation between the macro and microkinetic characteristics of porous electrode operation, based on the example of a liquid porouse electrode at a steady-state operation, reactant supply and products removal being forced. 6 figs, 8 refs.

29. Properties of porous electrodes and possibilities of their use in futur generators-

M. Bonnemay and G. Bronoel, Trans. SAEST, 6-2(1971)63. The type of electrodes that could be improved so that they could be used in generators. The basic phenomena that characterise the triple contact electrode - advantages and disadvantages. Dispersed electrodes constitute an important development. 5 figs, 19 refs.

30. A comparison of various 24K gold electrodeposits-

S. E. Craig et al., J. Electrochem. Soc., 117-11 (1970) 1450. Gold prepared from 14 types of plating solutions and examined by x-ray, SEM, gravimetric and electrical techniques.

31. Effects of plating conditions on crystal grains of gold deposits obtained from citrate bath-

I. Yoshizawa et al., Kinzoku Hyomen Gijutsu, 21-8 (1970) 416 Gold Bull. 4-2 (1971) 37. The effects of $KAu(CN)_2$ and c.d. on grain size and twinning in Au deposits.

32. Corrsoion resistance of zirconium and its alloys in chemicals–

H.Demars,Korr figyelo (Hung.) 11-2 (1971) 51. Zirconium has good resistance in most aggressive media. Its behavier in several media, especially its behaviour is HS_2O_4 and HCl as a function of several metallurgical and chemical parameters. These two media, usually used in chemical industry, give serious corrosion problems that zirconium can effectively solve. Table, 11 figs, 16 refs.

33. The pigments in paints : Part 5-

H. P. Preuss, Metal Finish., 69-5 (1971) 85. The author continues the review. This paper deals with color pigments in general and the brown pigments in particular. 4 tables, 7 refs.

34. Microcrystalline abrasive media for mass finishing-

M. Matsunaga, Metal Finish., 69-5 (1971) 97. Discusses the effectiveness of sintered Al_2O_3 and other abrasives in barrel finishing. 4 tables, 11 figs, 36 refs.

35. Investigations on the thermal decomposition of cyanide solid wastes–

M. Kieszkowski, Electrop'ating Metal Finish., 24-5 (1971) 5. Examinations carried out on a laboratory scale for hydrated sludge from periodical cleaning of zinc plating tanks. 2 tables, 6 figs, 6 refs.

—K.I.V.

B. ELECTROMETALLURGY AND METALLURGY

1. Filler materials for welding-

Axel Bernstein, Tool and Alloy Steels, 5-2 (1971)8. Discusses the requirements on stainless steel welds of importance for the filler material. In certain corrossion environments, e.g. in the urea industry, ferrite in the welds may result in a type of intergranular corrosion, and it is required to keep the ferrite to a minimum. 3 figs, 3 refs.

2. Modern developments in welding technology-

V. Ramamrutham, Tool and Alloy Steels, 5-2(1971)13. Discusses such of the modern techniques as ultra-sonic welding, laser welding, electron beam welding and plasma arc welding.

3. Submerged arc welding technology-

N.S.Subbanna, Tool and Alloy Steels, 5.2(1971)19. Discusses the development of these equipments in India.

4. Maintenance Welding Techniques in steel plants-

D. K. Roy, Tool and Alloy Steels, 5-2(1971)21. Discusses the guiding factors in maintenance in practice. 2 Tabs, 3 figs, 8 refs.

5. Amorphous, glassy and liquid semiconductors-

E. A. Davis, Phys. Bull., 22 (1971)81. Discusses the preparation and classification, structure, electrical properties, optical properties and the theory and models for amorphous and liquid semticonductors and their applications. 13 figs, 31 refs.

6. Technical possibilities and advantages of the coil coating of aluminium strip-

I. Komjati, Korr. figyelo, 10-6 (1970) 201 (Hung.) The protective effect due to the superficial oxide layer on aluminium may be increased partly by methods pf pre-treatment and partly by employing additional materials. These include the materials, equipment and methods for the coil coating of aluminium products before fabrication. 4 tables, 3 figs, 41 refs.

7. Recent advances in extraction metallurgy- (A) Hydrometallurgy- (B) Electrometallurgy-

A. R. Burkin, and J. Mackowiak, Met. Review No. 151, Metals Mateials, 5-3 (1971) 47. Reviews the advances in leaching and solvent extraction.

Electrowinning and refining from aqueous of Cu, Ni, Zn, Cd, Co, Mn, Cr, Ga, Ag, Au, Sn and other metals. Electrowinning from fused electrolytes of Al, Mg, rare-earths, Ti and other metals. 126 refs.

8. Vacuum metallizing metals and plastics-

S. Kut, Metal Finish J., 17-194 (1970) 40. Concluding section includes performance requirements. Plastics and their uses, design considerations, glare and performance. 9 refs.

9. Adhesion of nylon to mild Steel-

J. C. Sherlock, Metal Finish. J., 17–195 (1971) 76. Effect of temp., surface treatment and humidity on adhesion of nylon to mild steel. Phosphating improves adhesion, fine grained phosphate coatings being preferred. 2 tables, 2 figs. 15 refs.

10. Plating on aluminium-

K. S. Indira, R. Subramanian and B. A. Shenoi, Metal Finish, 69-4 (1971) 53. Discusses anodizing as as a pre-treatment. 4 tables, 7 figs, 17 refs.

11. Electrical Contacts-

A. F. Bogenschutz, Galvanotech., 62-4 (1971) 265. The problem of electrical contact making in micro-miniaturisation of electronic components. Modern processes of electrolytic and electroless metal deposition as well as suitable etching processes solve this problem. 5 tables, 7 figs, 42 refs.

12. Mechanical and chemical influences during surface finishing–

H.E. Hinz, Galvanotech., 62-4 (1971) 298. Importance of mechanical and chemicel influences in the surface treatment. Chemical additives along with several innovations in the field of bulk finishing.

13. Effect of the conditions of electrolysis on the magnetic properties of highly dispersed cobalt-

T. M. Shvets et al., Poroshkovaya Met., 8 (1969) 1; Cobalt Abs., 50-06 (1971). The effect of $CoCl_2$ conc., c.d., and acidity on the magnetic properties of highly dispersed Co required for use in permanent magnets and magnetic tape.

14. Electron-microscope study of highly dispersed cobalt-

T.M. Shvets et al, Ukr. Khim. Zh., 36 (1970) 335; Cobalt Abs., 50-07 (1971). The shape and size of highly dispersed Co

particles obtained by electrodeposition under various conditions were studied by transmission electron microscopy.

15. Oxidation of Co-10 w/o Cr interupted by vacuum annealing-

P.K. Kofstad and A. Z. Hed. Oxid. Metals, 2-1 (1970) 101; Cobalt Abs., 50-17 (1971). Influence of vacuum annealing on the oxidation of Co-10 wt.% Cr was studied at 900° and 1100°C in 100 torr 0_2. The post-treatment oxidation rates were found to decrease markedly with the length of the vacuum annealing period. It is assumed that the decrease of the oxidation rate is due to ano increase in the amount of $Co\,Cr_2\,O_4$ in the inner layer.

16. Choice of electrolyte for the electrochemical machining of hard alloys of the WC-Co type-

V. V. Parshutin and Yu. N. Petrov, Electro. Obrabot. Mat., 6 (1969) 17; Cobalt Abs., 50-143 (1971). The electrochemical machining of hard alloys of the WC-Co type was studied in solutions of NaCl, Na_2CO_3, NaOH and $NaNO_3$ of various conc. The best result in NaOH-$NaNO_3$ mixture.

17. Wear of electrode tools in electrochemical machining-

V. V. Paustovskii, Poroshkovaya. Met, 4 (1970) 60; Cobalt Abs., 50-146 (1971). The greatest wear resistance is exhibited by the WC-Co group of alloys. The hard alloys of the TiC-Co group tend to wear as a result of mutual diffusion between the elements in the electrodes and those in the metal being machined.

18. Surface oxidation of zinc in the range 300 to 400°C-

R. W. Lucas, J. Inst. Metals,99 (1971) 69. Oxidation of zinc single crystals is slightly orientation dependent. Copious whisker growth on surface and some evidence of epitaxy were observed. Addition of Pb, Fe and Al reduced the rate of oxidation. In SO_2, the surface film is $ZnSO_4$. 14 figs. 17 refs.

19. The effect of Cu and Ag on the stress corrosion of Al-Zn-Mg alloys-

J. Busby, J.F. Cleave and R.L. Cund, J.Inst. Metals, 99(1971)41. Addition of Cu or Ag improve stress-corrosion-resistance of Al-Zn-Mg alloys and weldments without reducing the weldability. The presence of these elements also permits weldments to be given a post-weld artificial ageing treatment to produce significantly higher-strength joints without impairing the S. C. resistance. 6 tables, 1 Fig., 16 refs.

20. Stress-corrosion of welded Al-Zn-Mg alloys.

J. M. Truscott, V.E. Carter and H.S. Campbell, J. Inst. Metals, 99 (1971)57. Tests show a limit of Zn and mg content for high resistance to SCC. The effect of Additions of Ag or Cu, of grain structure and heat-treatment and of the welding process on SCC has been investigated. 11 tables. 2 figs. 3 refs.

21. Operating experience with electrolytes containing LiF-

G.Wendt. Met. Trans., 2(1971) 155. Addition of lithiam salts to the cryolite bath results in economic benefits under special conditions. Voltage, power, anode paste and fluorine electrolyte consumptions are lower; current efficiency is increased, but alumina solubility is decreased. 15 figs, 47 refs.

22. Determination of metal and current efficiency in commercial aluminium reduction cell-

K.Gryotheim, et al, Met.Trans., 2(1971)199. Radioisotopic dilution technique. The method allows a determination of the current efficiency over a period of 2 to 3 days. 2 tables, 9 figs, 5 refs.

23. Codeposition of Al_2O_3 and TiO_2 with copper-

E.S.Chen, G. R. Laxminarayanan and F.K.Sautter, Met.Trans., 2(1971)937. Codeposition of Al_2O_3 and TiO_2 from the acid copper electrolyte was investigated with respect to pH, particle conc., addition agents and nature of the oxide particles. The incorporation of oxides was possible with out addition agents, provided the oxide particles are of the favourable crystalline from as alpha Al_2O_3 and rutile TiO_2. 5 tables, 6 figs, 10 refs.

24. Oxidation of T D Nickel between 900 and 1200°C-

C.S. Giggins and F.S. Petit, Met. Trans. 2 (1971) 1071.

Oxidation of TDNickel(Ni-20Cr-2% ThO_2) between 900° and 1200°C. Cr is selectively oxidized, and the parabolic rate constants for the growth of the resulting Cr_2O_3 layer are about on order of magnitude lower than those for the growth of Cr_2O_3 on a simple Ni-Cr alloy. ThO_2 dispersion improve the oxidation properties of this alloy by promoting the selective oxidation of Cr and decreasing the growth rate of Cr_2O_3 scale. 2 tables, 11 figs, 18 refs.

25. Stress corrosion in Al-Zn-Mg alloys-

I.T. Taylor and R. L. Edgar, Met. Trans. 2 (1971) 833. Specific combinations of mechanical and thermal conditions necessary for SCC. The high corrosion potential at grain boundaries in susceplible Al-Zn-Mg alloys is due to segregation of Zn and Mg. By taking precautions to reduce this segregation, the SC life can be increased. 6 tables, 13 figs, 29 refs.

26. Corrosion of aluminium-boron composites in chloride solutions-

A.J. Sedriks, J.A.S. Green and D.L. Novak, Met. Trans. 2(1971) 871. Corrosion behaviour of diffusion bonded Al-boron filament composites in aq. chloride solutions. Compared with the 2024 aluminium alloy, the composites suffer greater localized corrosion, both in the presence and absence of applied stress, not due to galvanic action between the filament and matrix, but from an increase in the number of anodic sites. 3 tables, 6 figs, 11 refs.

27. Martensite in NiAl oxidation resistant coatings-

J. L. Smialek, Met. Trans. 2 (1971) 913. The striated microstructures in NiAl oxidation resistant coatings result from a mertensitic transformation in NiAl. 4 figs. 4 refs.

28. Deformation of titanium by serface oxidation-

H. Kellerer and L. Wingert, Met. Trans. 2 (1971) 113. The length changes by oxidation on a selected surface of Ti-6Al-4V between 800° and 1040°C result in a bimetallic strip effect. Of the several mechanisms, the one based on the increase of the C-lattice parameter with increasing oxygen content accounts for most of the observed volume expansion. These introduce stresses which result in extensive creep deformation. 6 figs, 8 refs.

29. Preventing stress-corrosion cracking in high-strength aluminium forgings-

E.A. Lauchner, Metals Eng. Quartery, 11-2(1971) 47. Design factors, changing material or temper, processing controls, protective coatings etc.

30. Aluminium-manganese codeposit for protection of castings-

Metals Materials, 5-4(1971) 116 An Al-Mn alloy plating system has been developed, more durable, less costly and an attractive alternative to cadmium plating for corrosion protection. The coating process is conducted in a relatively low-temp. fused salt electrolyte at 350°C. No hydrogen is introduced into the steel during plating, thus reducing the chances of hydyogen embrittlement.

31. Vacuum-deposited chromium coatings on steel-

L.E. Helwig, L.L. Lewis and M.V. Murray, Metal Finish.,69-5 (1971) 90. Describes a procedure to make vacuum-deposited chromium coatings on steel equivalent in performance to electroplated coatings.

32. Safety considerations in the use of powder coatings-

S. Kut, Metal Finish., 69-5 (1971) 109. Briefly summarize some of the basic factors involved in the handling of dusts. Characteristics of dust explosions, factors influencing dust explosions and safety aspects. 16 refs.

33. Some observations on the surface topography and corrosion resistance of black chrome-

J.K. Dennis and J. J. Fuggle, Electroplating Metal Finish.,24-4 (1971) 5. Methods of examining the surface of black chrome deposits and of investigating the characteristics of corrosion pits developed after exposure to the CASS test. 13 figs, 5 refs.

—K.I.V.